

DPC-12-350

DPC-12-350 Information



Part Number	DPC-12-350	
Manufacturer	Signal Transformer	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 4.4VA THRU HOLE	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DPC-12-350 Specifications

Manufacturer Part Number DPC-12-350 Manufacturer Signal Transformer Category Transformers Package - Series DPC Type Laminated Core Voltage - Primary ISV, 230V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 700mA, Series 350mA Primary Winding(s) Dual Secondary Winding(s) Dual Power - Max 4.4 VA Mounting Type Through Hole Size / Dimension 4.30mm L x 31.80mm W Size / Dimension Size / Dimension Voltage - Isolation Sizolation Size		
CategoryTransformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max4.4 VAMounting TypeThrough HoleSize / DimensionPC PinSize / Dimension34.92mmHeight - Seated (Max)500VrmsWeight0.313 lb (141.97g)	Manufacturer Part Number	DPC-12-350
Power TransformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleSize / Dimension41.30mm Lx 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Manufacturer	Signal Transformer
Package-SeriesDPCTypeLaminated CoreVoltage - Primary15V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleSize / Dimension4.130mm Lx 31.80mm WSize / Dimension34.92mmHeight - Seated (Max)500VrmsWeightSize / Size /	Category	Transformers
SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension4.130mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleStez / DimensionPC PinSize / Dimension4.130mm L x 31.80mm WHeight - Seated (Max)500VrmsWotght500Vrms	Package	-
Yoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.92mmHeight - Seated (Max)34.92mmWoltage - Isolation500VrmsWeight0.313 lb (141.97g)	Series	DPC
Voltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Туре	Laminated Core
Current - Output (Max)Parallel 700mA, Series 350mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.92mm L x 31.80mm WHeight - Seated (Max)1500VrmsVoltage - Isolation0.313 lb (141.97g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Current - Output (Max)	Parallel 700mA, Series 350mA
Center TapNoPower - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Primary Winding(s)	Dual
Power - Max4.4 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Center Tap	No
Termination StylePC PinSize / Dimension41.30mm L x 31.80mm WHeight - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Power - Max	4.4 VA
Size / Dimension 41.30mm L x 31.80mm W Height - Seated (Max) 34.92mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Mounting Type	Through Hole
Height - Seated (Max)34.92mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Size / Dimension	41.30mm L x 31.80mm W
Weight 0.313 lb (141.97g)	Height - Seated (Max)	34.92mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.313 lb (141.97g)
		Report errors?

DPC-12-350 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

VICE Serv

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DPC-12-350, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com