

DPC-120-85B39 Information

Heisener.com

Part Number DPC-120-85B39

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 10VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPC-120-85B39 Specifications

Manufacturer DPC-120-85B39 Manufacturer Pulse Electronics Power Category Transformers Package - Series PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 170mA, Series 85mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) 41.28mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)		
CategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 170mA, Series 85mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 36.53mm WHeight - Seated (Max)41.28mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g)	Manufacturer Part Number	DPC-120-85B39
Package Power Transformers Package PC Plug-In Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 170mA, Series 85mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Vernation Style Size / Dimension Voltage - Isolation Voltage - Isolation Voltage - Isolation Oceanic Transformers PC Plug-In Laminated Core Parallel 60V, Series 120V Parallel 170mA, Series 85mA Primary Winding(s) Dual Parallel 170mA, Series 85mA Primary Winding(s) Pual Parallel 170mA, Series 85mA Primary Winding(s) Pual Parallel 170mA, Series 85mA Primary Winding(s) Parallel 60V, Series 120V Parallel 60V, Series 120	Manufacturer	Pulse Electronics Power
Package-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 170mA, Series 85mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 36.53mm WHeight - Seated (Max)41.28mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g)	Category	Transformers
SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 60V, Series 120VCurrent - Output (Max)Parallel 170mA, Series 85mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 36.53mm WHeight - Seated (Max)41.28mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 170mA, Series 85mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) 41.28mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 60V, Series 120V Current - Output (Max) Parallel 170mA, Series 85mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) Voltage - Isolation Weight 1500Vrms Weight	Series	PC Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 170mA, Series 85mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 60V, Series 120V Parallel 170mA, Series 85mA Pual Pual No 10 VA 41.28mm 1500Vrms 0.563 lb (255.37g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) Voltage - Isolation Veight Parallel 170mA, Series 85mA Dual Pual Poul No	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight	Voltage - Secondary (Full Load)	Parallel 60V, Series 120V
Secondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 36.53mm WHeight - Seated (Max)41.28mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g)	Current - Output (Max)	Parallel 170mA, Series 85mA
Center TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 36.53mm WHeight - Seated (Max)41.28mmVoltage - Isolation1500VrmsWeight0.563 lb (255.37g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) 41.28mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Center Tap	No
Termination Style PC Pin Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) 41.28mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Power - Max	10 VA
Size / Dimension 47.63mm L x 36.53mm W Height - Seated (Max) 41.28mm Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.563 lb (255.37g)	Size / Dimension	47.63mm L x 36.53mm W
Weight 0.563 lb (255.37g)	Height - Seated (Max)	41.28mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.563 lb (255.37g)
		Report errors?

DPC-120-85B39 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPC-120-85B39 Payment Methods



















DPC-120-85B39 Shipping Methods













If you have any question about DPC-120-85B39, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com