

# **DPC-24-50**

#### **DPC-24-50 Information**



Part Number	DPC-24-50	
Manufacturer	Signal Transformer	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 1.2VA THRU HOLE	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **DPC-24-50** Specifications

ManufacturerSignal TransformerCategoryTransformersPower TransformersPower TransformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StyleSecondaru & 34.90mm L x 28.60mm WHeight - Seated (Max)J500Vrms		
CategoryTansformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)500VrmsWoight1.500Vrms	Manufacturer Part Number	DPC-24-50
Power TransformersPackage-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)500VrmsWoight1500Vrms	Manufacturer	Signal Transformer
Package-SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StyleS4.90mm Lx 28.60mm WNieght - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Category	Transformers
SeriesDPCTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StyleSel 2400mm WSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)500VrmsWotage - Isolation1500VrmsWeight0.188 lb (85.28g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)500VrmsWotage - Isolation1500VrmsWeight0.188 lb (85.28g)	Package	-
Voltage - PrimaryInformationVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Series	DPC
Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Туре	Laminated Core
Current - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1.500VrmsWeight0.188 lb (85.28g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Current - Output (Max)	Parallel 100mA, Series 50mA
Center TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Primary Winding(s)	Dual
Power - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Secondary Winding(s)	Dual
Nounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Center Tap	No
Termination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Power - Max	1.2 VA
Size / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Mounting Type	Through Hole
Height - Seated (Max)30.15mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Size / Dimension	34.90mm L x 28.60mm W
Weight 0.188 lb (85.28g)	Height - Seated (Max)	30.15mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.188 lb (85.28g)
		Report errors?

#### **DPC-24-50** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DPC-24-50, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com