

DPC-24-50B17

DPC-24-50B17 Information

Heisener.com Betal terver statutier	Part Number Manufacturer Category Description Package	DPC-24-50B17 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 1.2VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DPC-24-50B17 Specifications

Manufacturer Part NumberDPC-24-50B17ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VOurpurt - Output (Max)Parallel 100MA, Series 50MASecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleSize / Dimension34.93mm Lx 28.58mm WSize / DimensionSolowrmaVoltage - Isolation1.500VrmsWeightSolowrmaSecondary (Solowrma)SolowrmaSecondary Winding SolowrmaSolowrmaSecondary Winding SolowrmaSolowrmaSecondary Winding SolowrmaSolowrmaSecondary Winding SolowrmaSolowrmaSecondary Winding SolowrmmaSolowrmaSecondary Winding SolowrmmaSolowrmaSecondary Winding SolowrmmaSolowrmmaSecondary W		
CategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max1.2 VAMounting TypeThrough HoleSize / Dimension34.93mm Lx 28.58mm WHeight - Seated (Max)500VrmsWeight1500Vrms	Manufacturer Part Number	DPC-24-50B17
InstrumPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleSize / Dimension34.93mm Lx 28.58mm WHeight - Seated (Max)500VrmsVoltage - Isolation500VrmsWeight0.188 lb (85.28g)	Manufacturer	Pulse Electronics Power
Package-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary15V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleSize/ Dimension34.93mm L x 28.58mm WHeight - Seated (Max)500VrmsWeight1500Vrms	Category	Transformers
SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StyleSecondary Minding(s)Size / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)500VrmsWeightStall (Mascale)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination Style92 PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)1500VrmsWoltage - Isolation1500Vrms	Package	-
YaNameVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StyleSecondary Winding(s)Size / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)1500VrmsVoltage - Isolation0.188 lb (85.28g)	Series	PC Plug-In
Voltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1.00VrmsWeight0.188 lb (85.28g)	Туре	Laminated Core
Current - Output (Max)Parallel 100mA, Series 50mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1500Vrms	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)S00VrmsVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Current - Output (Max)	Parallel 100mA, Series 50mA
Center TapNoPower - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Primary Winding(s)	Dual
Power - Max1.2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Center Tap	No
Termination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Power - Max	1.2 VA
Size / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Mounting Type	Through Hole
Height - Seated (Max)30.18mmVoltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.188 lb (85.28g)	Size / Dimension	34.93mm L x 28.58mm W
Weight 0.188 lb (85.28g)	Height - Seated (Max)	30.18mm
	Voltage - Isolation	1500Vrms
	Weight	0.188 lb (85.28g)
Report error		Report errors?

DPC-24-50B17 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DPC-24-50B17 Payment Methods



DPC-24-50B17 Shipping Methods



If you have any question about DPC-24-50B17, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com