

DPC-34-25B59 Information

Heisener.com

Part Number DPC-34-25B59

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 1VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPC-34-25B59 Specifications

Manufacturer Part NumberDPC-34-25B59ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 50mA, Series 25mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension25.40mm L x 34.93mm WHeight - Seated (Max)21.08mmVoltage - Isolation1500Vrms		
CategoryTransformersPackage-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 50mA, Series 25mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension25.40mm L x 34.93mm WHeight - Seated (Max)21.08mm	Manufacturer Part Number	DPC-34-25B59
Package - Series PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 50mA, Series 25mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max)	Manufacturer	Pulse Electronics Power
Package-SeriesPC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 17V, Series 34VCurrent - Output (Max)Parallel 50mA, Series 25mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension25.40mm L x 34.93mm WHeight - Seated (Max)21.08mm	Category	Transformers
Series PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 50mA, Series 25mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 125.40mm L x 34.93mm W Height - Seated (Max) 21.08mm		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 50mA, Series 25mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max) 21.08mm	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 50mA, Series 25mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style Size / Dimension Bize / Dimension Height - Seated (Max) 1 15V, 230V Parallel 17V, Series 34V Parallel 50mA, Series 25mA Dual Dual Poul No 1 VA 1 VA 2 1.08mm	Series	PC Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 50mA, Series 25mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max)	Туре	Laminated Core
Current - Output (Max) Parallel 50mA, Series 25mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max)	Voltage - Secondary (Full Load)	Parallel 17V, Series 34V
Secondary Winding(s)DualCenter TapNoPower - Max1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension25.40mm L x 34.93mm WHeight - Seated (Max)21.08mm	Current - Output (Max)	Parallel 50mA, Series 25mA
Center TapNoPower - Max1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension25.40mm L x 34.93mm WHeight - Seated (Max)21.08mm	Primary Winding(s)	Dual
Power - Max 1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max) 21.08mm	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max) 21.08mm	Center Tap	No
Termination Style PC Pin Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max) 21.08mm	Power - Max	1 VA
Size / Dimension 25.40mm L x 34.93mm W Height - Seated (Max) 21.08mm	Mounting Type	Through Hole
Height - Seated (Max) 21.08mm	Termination Style	PC Pin
2-1-8-1-1	Size / Dimension	25.40mm L x 34.93mm W
Voltage - Isolation 1500Vrms	Height - Seated (Max)	21.08mm
	Voltage - Isolation	1500Vrms
Weight 0.157 lb (71.21g)	Weight	0.157 lb (71.21g)
Report errors?		Report errors?

DPC-34-25B59 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPC-34-25B59 Payment Methods





















DPC-34-25B59 Shipping Methods













If you have any question about DPC-34-25B59, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com