

DPC-56-180 Information

Heisener.com

Part Number DPC-56-180

Manufacturer Signal Transformer

Category

Transformers **Power Transformers**

Description

XFRMR LAMINATED 10VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPC-56-180 Specifications

Manufacturer Part Number Manufacturer Category Transformers Power Transformers Package - Series DPC Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Center Tap Power - Max Mounting Type Through Hole Termination Style Size / Dimension Signal Transformer Signal Transformer Signal Transformer Signal Transformer Laminated Core 115V, 230V Parallel 28V, Series 56V Current - Output (Max) Parallel 360mA, Series 180mA Dual Through Hole Power - Max Mounting Type Through Hole PC Pin Size / Dimension 47 60mm L x 36 50mm W	<u> </u>	
Category Transformers Power Transformers Package Series DPC Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 360mA, Series 180mA Primary Winding(s) Secondary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	DPC-56-180
Package Series DPC Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style PPC Laminated Core Laminated Core Laminated Core DPC Laminated Core Laminated Core DPC Dual DPC	Manufacturer	Signal Transformer
Package - DPC Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 360mA, Series 180mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin	Category	Transformers
Series Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 360mA, Series 180mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style DPC Laminated Core Laminated Core 115V, 230V Parallel 28V, Series 56V Dual Dual Through Hole PC Pin		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 360mA, Series 180mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style 115V, 230V Parallel 28V, Series 56V Parallel 360mA, Series 180mA Poual Dual Through Hole PC Pin	Series	DPC
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 28V, Series 56V Parallel 360mA, Series 180mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Parallel 28V, Series 56V Parallel 26V, Series 56V Parallel 28V, Series 56V Paralle	Type	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 10 VA Mounting Type Through Hole Termination Style Parallel 360mA, Series 180mA Dual Dual Poul Poul Poul Poul Poul Poul Poul Pou	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Dual No Power Power Through Hole PC Pin	Voltage - Secondary (Full Load)	Parallel 28V, Series 56V
Secondary Winding(s)DualCenter TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC Pin	Current - Output (Max)	Parallel 360mA, Series 180mA
Center TapNoPower - Max10 VAMounting TypeThrough HoleTermination StylePC Pin	Primary Winding(s)	Dual
Power - Max 10 VA Mounting Type Through Hole Termination Style PC Pin	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin	Center Tap	No
Termination Style PC Pin	Power - Max	10 VA
·	Mounting Type	Through Hole
Size / Dimension 47.60mm U. v. 36.50mm W	Termination Style	PC Pin
5120 / Dimension 47.00mm W	Size / Dimension	47.60mm L x 36.50mm W
Height - Seated (Max) 41.27mm	Height - Seated (Max)	41.27mm
Voltage - Isolation 1500Vrms	Voltage - Isolation	1500Vrms
Weight 0.563 lb (255.37g)	Weight	0.563 lb (255.37g)
Report errors?		Report errors?

DPC-56-180 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPC-56-180 Payment Methods



















DPC-56-180 Shipping Methods













If you have any question about DPC-56-180, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com