



Heisener.com

DPD060020-P6/RN-SZ Information

Part Number DPD060020-P6/RN-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 6V 1W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD060020-P6/RN-SZ Specifications

Manufacturer Part Number DPD060020-P6/RN-SZ Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120 VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Manufacturer Part Number	DPD060020-P6/RN-SZ
AC DC Desktop, Wall Adapters Package Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension AC DC Desktop, Wall Adapters - Consider Adapters North America 120VAC Wall Mount 120VAC Voltage - Output 6V Current - Output (Max) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Consider America - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Consider America - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Consider America - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Cuput Connector Size / Dimension AC DC Desktop, Wall Adapters - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension AC DC Desktop - Cuput Connector Size / Dimension - Cuput Connector Size / Dimensio	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 120VAC 6V Current - Output (Max) 1.2W No Load Power Consumption - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Form	Wall Mount
Voltage - Output (Max) 200mA Power (Watts) 1.2W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Input Type	Fixed Blade
Current - Output (Max) 200mA 1.2W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 200mA 1.2W Negative Center ITE (Commercial) - Commercial) - Commercial	Voltage - Input	120VAC
Power (Watts) 1.2W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 1.2W Negative Center ITE (Commercial) - Output Commercial) 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Voltage - Output	6V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Current - Output (Max)	200mA
Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Power (Watts)	1.2W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Polarization	Negative Center
Operating Temperature Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Efficiency	-
Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm
Report errors?	Size / Dimension	2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)
		Report errors?

DPD060020-P6/RN-SZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD060020-P6/RN-SZ Payment Methods



















DPD060020-P6/RN-SZ Shipping Methods













If you have any question about DPD060020-P6/RN-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com