

# DPD060025-P12P-DK

## DPD060025-P12P-DK Information

Heisener.com

Part Number DPD060025-P12P-DK

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 6V 2W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DPD060025-P12P-DK Specifications

Manufacturer Part Number         DPD060025-P12P-DK           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Reckage         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         6V           Current - Output (Max)         500mA           Power (Watts)         3W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm           Size / Dimension         2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         6V           Current - Output (Max)         500mA           Power (Watts)         3W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm           Size / Dimension         2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Manufacturer Part Number	DPD060025-P12P-DK
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         6V           Current - Output (Max)         500mA           Power (Watts)         3W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm           Size / Dimension         2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         6V           Current - Output (Max)         500mA           Power (Watts)         3W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm           Size / Dimension         2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         6V           Current - Output (Max)         500mA           Power (Watts)         3W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm           Size / Dimension         2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 6V Current - Output (Max) 500mA Power (Watts) 3W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 6V  Current - Output (Max) 500mA  Power (Watts) 3W  No Load Power Consumption -  Polarization Positive Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Series	-
Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 6V  Current - Output (Max) 500mA  Power (Watts) 3W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Region Utilized	North America
Voltage - Input  120VAC  Voltage - Output  6V  Current - Output (Max)  500mA  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension  120VAC  6V  Current - Output (Max)  500mA  No Load Power Consumption  -  Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension  2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Form	Wall Mount
Voltage - Output (Max) 500mA  Power (Watts) 3W  No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Input Type	Fixed Blade
Current - Output (Max)  500mA  Power (Watts)  No Load Power Consumption  - Polarization  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension  500mA  3W  - Current - Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Voltage - Input	120VAC
Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension  2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Voltage - Output	6V
No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension  2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Current - Output (Max)	500mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Power (Watts)	3W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Polarization	Positive Center
Operating Temperature  Output Connector  Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm  Size / Dimension  2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm           Size / Dimension         2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Efficiency	-
Size / Dimension 2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 0.7mm I.D. x 2.4mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.33" L x 1.50" W x 1.35" H (59.2mm x 38.0mm x 34.2mm)
		Report errors?

#### DPD060025-P12P-DK Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DPD060025-P12P-DK Payment Methods



















## DPD060025-P12P-DK Shipping Methods













If you have any question about DPD060025-P12P-DK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com