



### DPD090050E-P5N Information

Heisener.com

Part Number DPD090050E-P5N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 9V 5W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DPD090050E-P5N Specifications**

Manufacturer Part Number         DPD090050E-P5N           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         220VAC           Voltage - Output         9V           Current - Output (Max)         500mA           Power (Watts)         4.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         220VAC           Voltage - Output         9V           Current - Output (Max)         500mA           Power (Watts)         4.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Manufacturer Part Number	DPD090050E-P5N
Package         -           Series         -           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         220VAC           Voltage - Output         9V           Current - Output (Max)         500mA           Power (Watts)         4.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         220VAC           Voltage - Output         9V           Current - Output (Max)         500mA           Power (Watts)         4.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         Europe           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         220VAC           Voltage - Output         9V           Current - Output (Max)         500mA           Power (Watts)         4.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)		AC DC Desktop, Wall Adapters
Region UtilizedEuropeFormWall MountInput TypeFixed BladeVoltage - Input220VACVoltage - Output9VCurrent - Output (Max)500mAPower (Watts)4.5WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 220VAC  Voltage - Output 9V  Current - Output (Max) 500mA  Power (Watts) 4.5W  No Load Power Consumption -  Polarization Negative Center Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension x 41.5mm)	Series	-
Input Type Fixed Blade  Voltage - Input 220VAC  Voltage - Output 9V  Current - Output (Max) 500mA  Power (Watts) 4.5W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 22.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Region Utilized	Europe
Voltage - Input  220VAC  Voltage - Output  9V  Current - Output (Max)  500mA  Power (Watts)  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Form	Wall Mount
Voltage - Output 9V  Current - Output (Max) 500mA  Power (Watts) 4.5W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension 2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  A.5W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  500mA  4.5W  A.5W  Center  ITE (Commercial)  -  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Voltage - Input	220VAC
Power (Watts)  4.5W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Voltage - Output	9V
No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Current - Output (Max)	500mA
Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Power (Watts)	4.5W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Polarization	Negative Center
Operating Temperature  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Efficiency	-
Size / Dimension 2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	2.32" L x 1.97" W x 1.63" H (59.0mm x 50.0mm x 41.5mm)
		Report errors?

#### **DPD090050E-P5N Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DPD090050E-P5N Payment Methods**





















## DPD090050E-P5N Shipping Methods













If you have any question about DPD090050E-P5N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com