

DPD090100-P14P-TC

DPD090100-P14P-TC Information

Heisener.com

Part Number DPD090100-P14P-TC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 9V 9W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD090100-P14P-TC Specifications

Manufacturer Part Number DPD090100-P14P-TC Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Reckage - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Manufacturer Part Number	DPD090100-P14P-TC
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 120VAC 9V 14 16 17 18 18 19 19 19 10 10 10 10 10 10 10	Form	Wall Mount
Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Voltage - Output	9V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Current - Output (Max)	1A
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Power (Watts)	9W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Polarization	Positive Center
Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Efficiency	-
Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)
		Report errors?

DPD090100-P14P-TC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD090100-P14P-TC Payment Methods



















DPD090100-P14P-TC Shipping Methods













If you have any question about DPD090100-P14P-TC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com