

Heisener.com

# DPD090100-P7/RN-TC

### DPD090100-P7/RN-TC Information

Part Number DPD090100-P7/RN-TC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 9V 9W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# DPD090100-P7/RN-TC Specifications

| Manufacturer Part Number         DPD090100-P7/RN-TC           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Rekage         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output (Max)         1A           Power (Watts)         9W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm) |                           |  |
|--|---------------------------|--|
| Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         1A           Power (Watts)         9W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)                         | Manufacturer Part Number  | DPD090100-P7/RN-TC                                     |
| Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         1A           Power (Watts)         9W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Manufacturer              | CUI Inc.   |
| Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         1A           Power (Watts)         9W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Category                  | Power Supplies - External/Internal (Off-Board)         |
| Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output9VCurrent - Output (Max)1APower (Watts)9WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)   |                           | AC DC Desktop, Wall Adapters                           |
| Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1A Power (Watts) 9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension x 46.0mm)  | Package                   | -  |
| Form Wall Mount Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 9V  Current - Output (Max) 1A  Power (Watts) 9W  No Load Power Consumption -  Polarization Negative Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Series                    | -  |
| Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 9V  Current - Output (Max) 1A  Power (Watts) 9W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Region Utilized           | North America  |
| Voltage - Input  120VAC  Voltage - Output  9V  Current - Output (Max)  1A  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  120VAC  14  120VAC  9V  14  15  16  17  18  18  18  18  19  18  19  18  19  18  19  18  18  | Form                      | Wall Mount   |
| Voltage - Output 9V  Current - Output (Max) 1A  Power (Watts) 9W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Input Type                | Fixed Blade  |
| Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)   | Voltage - Input           | 120VAC   |
| Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)   | Voltage - Output          | 9V   |
| No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Current - Output (Max)    | 1A   |
| Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Power (Watts)             | 9W   |
| Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | No Load Power Consumption | -  |
| Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)   | Polarization              | Negative Center  |
| Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Applications              | ITE (Commercial)                                       |
| Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Efficiency                | -  |
| Size / Dimension 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm)  | Operating Temperature     | -  |
|  | Output Connector          | Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm       |
| Report errors?   | Size / Dimension          | 3.72" L x 2.32" W x 1.81" H (94.5mm x 59.0mm x 46.0mm) |
|  |                           | Report errors?   |

### DPD090100-P7/RN-TC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DPD090100-P7/RN-TC Payment Methods



















## DPD090100-P7/RN-TC Shipping Methods













If you have any question about DPD090100-P7/RN-TC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com