

Heisener.com

DPD120005-P13/RP-SZ

DPD120005-P13/RP-SZ Information

Part Number DPD120005-P13/RP-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC WALL MNT ADAPTER 12V 600MW **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD120005-P13/RP-SZ Specifications

Manufacturer Part Number DPD120005-P13/RP-SZ Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Manufacturer Part Number	DPD120005-P13/RP-SZ
AC DC Desktop, Wall Adapters Package Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120V AC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension AC DC Desktop, Wall Adapters - Acc DC Desktop, Wall Adapters - Commercial Applications ITE (Commercial) Size / Dimension AC DC Desktop, Wall Adapters Vall Adapters - Commercial Applications ITE (Commercial) Size / Dimension AC DC Desktop, Wall Adapters - Commercial Applications - Commercial AC DC Desktop, Wall Adapters - Commercial Applications - Commercial AC DC Desktop, Wall Adapters - Commercial Acc DC Desktop - Commercial AC DC Desktop, Wall Adapters - Commercial Acc DC Desktop - Commercial Acc D	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension Fixed Blade Fixed	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 50mA Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 120VAC 12V 12V 12V 12V 12V 12V 12V 12	Form	Wall Mount
Voltage - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Input Type	Fixed Blade
Current - Output (Max) 50mA Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Voltage - Input	120VAC
Power (Watts) 600mW No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Voltage - Output	12V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Current - Output (Max)	50mA
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Power (Watts)	600mW
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Polarization	Positive Center
Operating Temperature Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Efficiency	-
Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)
		Report errors?

DPD120005-P13/RP-SZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD120005-P13/RP-SZ Payment Methods



















DPD120005-P13/RP-SZ Shipping Methods













If you have any question about DPD120005-P13/RP-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com