



Heisener.com

DPD120020-P7/RN-SZ Information

Part Number DPD120020-P7/RN-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 2W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD120020-P7/RN-SZ Specifications

Manufacturer Part Number DPD120020-P7/RN-SZ Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Manufacturer Part Number	DPD120020-P7/RN-SZ
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 120VAC 12V 12V 12V 12V 12V 12V 12V 12	Form	Wall Mount
Voltage - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Input Type	Fixed Blade
Current - Output (Max) 200mA Power (Watts) 2.4W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Voltage - Input	120VAC
Power (Watts) 2.4W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Voltage - Output	12V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Current - Output (Max)	200mA
Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Power (Watts)	2.4W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Polarization	Negative Center
Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Efficiency	-
Size / Dimension 2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
Report errors?	Size / Dimension	2.15" L x 1.67" W x 1.46" H (54.6mm x 42.5mm x 37.0mm)
		Report errors?

DPD120020-P7/RN-SZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD120020-P7/RN-SZ Payment Methods





















DPD120020-P7/RN-SZ Shipping Methods













If you have any question about DPD120020-P7/RN-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com