

Heisener.com

DPD120030-P7/RP-TC

DPD120030-P7/RP-TC Information

Part Number DPD120030-P7/RP-TC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 4W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD120030-P7/RP-TC Specifications

Manufacturer Part Number DPD120030-P7/RP-TC Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.36" L. x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120 VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Manufacturer Part Number	DPD120030-P7/RP-TC
AC DC Desktop, Wall Adapters Package Series Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)300mAPower (Watts)3.6WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)300mAPower (Watts)3.6WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector 120VAC 12V 12V 12V 12V 300mA Positive Center - Commercial 15 (Commercial) 16 (Commercial) 17 (Commercial) 17 (Commercial) 18 (Commercial) 19 (Commercial) 10 (Commercial) 10 (Commercial) 11 (Commercial) 11 (Commercial) 12 (Commercial) 13 (Commercial) 14 (Commercial) 15 (Commercial) 16 (Commercial) 17 (Commercial) 18 (Commercial) 19 (Commercial) 10 (Commercial) 10 (Commercial) 11 (Commercial) 11 (Commercial) 12 (Commercial) 13 (Commercial) 14 (Commercial) 15 (Commercial) 16 (Commercial) 17 (Commercial) 17 (Commercial) 18 (Commercial) 19 (Commercial) 19 (Commercial) 10 (Commercial) 10 (Commercial) 11 (Commercial) 11 (Commercial) 12 (Commercial) 13 (Commercial) 14 (Commercial) 15 (Commercial) 16 (Commercial) 17 (Commercial) 18 (Commercial) 19 (Commercial) 19 (Commercial) 10 (Commercial) 10 (Commercial) 10 (Commercial) 11 (Commercial) 12 (Commercial) 13 (Commercial) 14 (Commercial) 15 (Commercial) 16 (Commercial) 17 (Commercial) 18 (Commercial) 19 (Commercial) 10 (Commercial) 10 (Commercial) 10 (Commercial) 10 (Commercial) 10 (Commercial) 11 (Commercial) 12 (Commercial) 13 (Commercial) 14 (Commercial) 15 (Commercial) 16 (Commercial) 17 (Commercial)	Form	Wall Mount
Voltage - Output (Max) 300mA Power (Watts) 3.6W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 3.6W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector 300mA 300mA 1.6W 1.6W 1.6W 1.7W 1.	Voltage - Input	120VAC
Power (Watts) 3.6W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Voltage - Output	12V
No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Current - Output (Max)	300mA
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Power (Watts)	3.6W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Polarization	Positive Center
Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm	Efficiency	-
	Operating Temperature	-
Size / Dimension 2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Output Connector	Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
	Size / Dimension	2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)
Report errors?		Report errors?

DPD120030-P7/RP-TC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD120030-P7/RP-TC Payment Methods



















DPD120030-P7/RP-TC Shipping Methods













If you have any question about DPD120030-P7/RP-TC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com