



# **DPD120030-Z7N Information**

Heisener.com

Part Number DPD120030-Z7N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 12V 4W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DPD120030-Z7N Specifications**

Manufacturer Part Number         DPD120030-Z7N           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output (Max)         300mA           Power (Watts)         3.6W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Manufacturer Part Number	DPD120030-Z7N
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         12V           Current - Output (Max)         300mA           Power (Watts)         3.6W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         12V           Current - Output (Max)         300mA           Power (Watts)         3.6W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120 VACVoltage - Output12VCurrent - Output (Max)300mAPower (Watts)3.6WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)300mAPower (Watts)3.6WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Package	-
FormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)300mAPower (Watts)3.6WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Series	-
Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 12V  Current - Output (Max) 300mA  Power (Watts) 3.6W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Region Utilized	North America
Voltage - Input  120VAC  Voltage - Output  12V  Current - Output (Max)  300mA  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  120VAC  12V  12V  12V  100mA  100mA	Form	Wall Mount
Voltage - Output Current - Output (Max) 300mA  Power (Watts) 3.6W  No Load Power Consumption Polarization Negative Center Applications ITE (Commercial)  Efficiency Operating Temperature Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension  12V  300mA  Negative Center	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  3.6W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Voltage - Input	120VAC
Power (Watts)  3.6W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Voltage - Output	12V
No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Current - Output (Max)	300mA
Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Power (Watts)	3.6W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Polarization	Negative Center
Operating Temperature  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Efficiency	-
Size / Dimension 2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
Report errors?	Size / Dimension	2.36" L x 1.99" W x 1.61" H (60.0mm x 50.5mm x 41.0mm)
		Report errors?

#### DPD120030-Z7N Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DPD120030-Z7N Payment Methods



















### **DPD120030-Z7N Shipping Methods**













If you have any question about DPD120030-Z7N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com