



DPD120050-Z1RP Information

Heisener.com

Part Number DPD120050-Z1RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 6W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD120050-Z1RP Specifications

| Manufacturer Part Number DPD120050-Z1RP Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) | | |
|--|---------------------------|--|
| CategoryPower Supplies - External/Internal (Off-Board)Package-Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)500mAPower (Watts)6WNo Load Power Consumption-PolarizationPositive Tip, Negative SleeveApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.0mmSize / Dimension- | Manufacturer Part Number | DPD120050-Z1RP |
| Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption - Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Manufacturer | CUI Inc. |
| Package-Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)500mAPower (Watts)6WNo Load Power Consumption-PolarizationPositive Tip, Negative SleeveApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.0mmSize / Dimension- | Category | Power Supplies - External/Internal (Off-Board) |
| Series - North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption - Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - Positive Tip, Negative Sleeve - Phono Plug, 3.5mm O.D. x 14.0mm | | AC DC Desktop, Wall Adapters |
| Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output12VCurrent - Output (Max)500mAPower (Watts)6WNo Load Power Consumption-PolarizationPositive Tip, Negative SleeveApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorPhono Plug, 3.5mm O.D. x 14.0mmSize / Dimension- | Package | - |
| Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption - Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Series | - |
| Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) 6W No Load Power Consumption - Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency - Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension Fixed Blade Fixed Blade Fixed Blade Fixed Blade 120VAC 12V 12V 6W Foundary Foundary Foundary Foundary Foundary Fixed Blade 120VAC 12V 12V 12V 12V 12V 12V 12V 12 | Region Utilized | North America |
| Voltage - Input 120VAC Voltage - Output 12V Current - Output (Max) 500mA Power (Watts) No Load Power Consumption Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12 | Form | Wall Mount |
| Voltage - Output Current - Output (Max) 500mA Power (Watts) No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension 12V 6W Current - Output (Max) 6W Foward | Input Type | Fixed Blade |
| Current - Output (Max) 500mA Fower (Watts) No Load Power Consumption Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension 500mA 6W 6W Current - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm | Voltage - Input | 120VAC |
| Power (Watts) No Load Power Consumption Polarization Applications Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension 6W OW Positive Tip, Negative Sleeve ITE (Commercial) | Voltage - Output | 12V |
| No Load Power Consumption Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Current - Output (Max) | 500mA |
| Polarization Positive Tip, Negative Sleeve Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Power (Watts) | 6W |
| Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | No Load Power Consumption | - |
| Efficiency - Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Polarization | Positive Tip, Negative Sleeve |
| Operating Temperature - Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Applications | ITE (Commercial) |
| Output Connector Phono Plug, 3.5mm O.D. x 14.0mm Size / Dimension - | Efficiency | - |
| Size / Dimension - | Operating Temperature | - |
| | Output Connector | Phono Plug, 3.5mm O.D. x 14.0mm |
| Report errors? | Size / Dimension | - |
| • | | Report errors? |

DPD120050-Z1RP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD120050-Z1RP Payment Methods



















DPD120050-Z1RP Shipping Methods













If you have any question about DPD120050-Z1RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com