



DPD240040-Z5N Information

Heisener.com

Part Number DPD240040-Z5N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC WALL MOUNT ADAPTER 24V 10W **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPD240040-Z5N Specifications

Manufacturer Part Number DPD240040-Z5N Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Manufacturer Part Number	DPD240040-Z5N
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output24VCurrent - Output (Max)400mAPower (Watts)9.6WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 24V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 120VAC 120VAC 14V 120VAC 14V 1400mA 1500mA 1600mA 1700mA 1700mA 1700m 1700	Form	Wall Mount
Voltage - Output Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Input Type	Fixed Blade
Current - Output (Max) 400mA Power (Watts) 9.6W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Voltage - Input	120VAC
Power (Watts) 9.6W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Voltage - Output	24V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Current - Output (Max)	400mA
Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Power (Watts)	9.6W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Polarization	Negative Center
Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Efficiency	-
Size / Dimension 3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	3.06" L x 2.19" W x 1.77" H (77.6mm x 55.6mm x 45.0mm)
		Report errors?

DPD240040-Z5N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPD240040-Z5N Payment Methods



















DPD240040-Z5N Shipping Methods













If you have any question about DPD240040-Z5N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com