



#### DPR050020-P6/R-SZ Information

Heisener.com

Part Number DPR050020-P6/R-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC WALL MOUNT ADAPTER 5V 1W **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### DPR050020-P6/R-SZ Specifications

Manufacturer Part Number         DPR050020-P6/R-SZ           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         200mA           Power (Watts)         IW           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         -           Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters  Package - Series - Region Utilized North America  Form Wall Mount Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output (Max) 200mA  Power (Watts) 1W  No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension -	Manufacturer Part Number	DPR050020-P6/R-SZ
Package-Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)200mAPower (Watts)1WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension-	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         200mA           Power (Watts)         1W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm           Size / Dimension         -	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output5VCurrent - Output (Max)200mAPower (Watts)1WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension-		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 200mA Power (Watts) 1W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension -	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 120 VAC  Voltage - Output 5V  Current - Output (Max) 200mA  Power (Watts) 1W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension -	Series	-
Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 5V  Current - Output (Max) 200mA  Power (Watts) 1W  No Load Power Consumption - Polarization Positive Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension -	Region Utilized	North America
Voltage - Input  120VAC  Voltage - Output  5V  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  120VAC  120VAC  100  100  100  100  100  100  100  1	Form	Wall Mount
Voltage - Output (Max) 200mA  Power (Watts) 1W  No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension -	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  200mA  1W	Voltage - Input	120VAC
Power (Watts)  No Load Power Consumption  Polarization  Applications  Efficiency  Operating Temperature  Output Connector  Size / Dimension  1W  Positive Center  Positive Center  ITE (Commercial)	Voltage - Output	5V
No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm  Size / Dimension  -	Current - Output (Max)	200mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension -	Power (Watts)	1W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension -	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension -	Polarization	Positive Center
Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension -	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension -	Efficiency	-
Size / Dimension -	Operating Temperature	-
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	-
		Report errors?

#### DPR050020-P6/R-SZ Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### DPR050020-P6/R-SZ Payment Methods



















## DPR050020-P6/R-SZ Shipping Methods













If you have any question about DPR050020-P6/R-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com