

# **DPS-750AB-26 C**

#### **DPS-750AB-26 C Information**

Heisener.com	 DPS-750AB-26 C Delta Electronics Power Supplies - External/Internal (Off-Board) AC DC Converters FLEXATX 750W - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **DPS-750AB-26 C Specifications**

Manufacturer Part Number   DPS-750AB-26 C     Manufacturer   Delta Electronics     Category   Power Supplies - External/Internal (Off-Board)     AC DC Converters   AC DC Converters     Package   -     Series   -     Type   Front End     Number of Outputs   6     Voltage - Input   180 ~ 264 VAC     Voltage - Output 1   12V     Voltage - Output 2   12V     Voltage - Output 3   12V     Voltage - Output 4   12V     Voltage - Output 5   6     Voltage - Output 6   12V     Voltage - Output 7   12V     Voltage - Output 8   12V     Voltage - Output 4   12V     Voltage - Output 4   12V     Voltage - Solation   -     Voltage - Isolation   -     Voltage - Isolation   -     Operating Tempe				
CategoryPower Supplies - External/Internal (Off-Board)Ac DC ConvertersPackage-Series-TypeFront EndNumber of Outputs6Voltage - Input180 ~ 264 VACVoltage - Output 112VVoltage - Output 212VVoltage - Output 312VVoltage - Output 412VVoltage - Output 412VVoltage - Output 590WVoltage - Output 612VVoltage - Output 790WVoltage - Output 612VVoltage - Output 790WVoltage - Output 612VVoltage - Output 790WVoltage - Output 690WPower (Watts)90WPower (Watts)90%Poltacions17E (Commercial)Voltage - Isolation-Fifticiency92%Operating Temperature9CPorc SorCFeaturesFeaturesPC, Remote On/Off, Remote Sense, Standby OutputFourting Type84M NutSize / Dimension945" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Manufacturer Part Number	DPS-750AB-26 C		
AC DC Converters     Package   -     Series   -     Type   Front End     Number of Outputs   6     Voltage - Input   180 ~ 264 VAC     Voltage - Output 1   12V     Voltage - Output 2   12V     Voltage - Output 3   12V     Voltage - Output 4   12V     Voltage - Output 5   600W     Current - Output (Max)   24A, 24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   FC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Kack Mount     Size / Dimension   945" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Manufacturer	Delta Electronics		
Package.Series.TypeFront EndNumber of Outputs6Voltage - Input180 ~ 264 VACVoltage - Output 112VVoltage - Output 212VVoltage - Output 312VVoltage - Output 412VVoltage - Output 424A, 24A, 24A, 24A, 18APower (Watks)MOWApplicationsTE (Commercial)Voltage - Isolation92%Operating Temperature9C ~ 50°CFeaturesFC, Remote On/Off, Remote Sense, Standby Output 40.0mm, 16UNouting Type945° L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series-TypeFront EndNumber of Outputs6Voltage - Input180 ~ 264 VACVoltage - Output 112VVoltage - Output 212VVoltage - Output 312VVoltage - Output 412VVoltage - Output 424A, 24A, 24A, 28A, 18APower (Watts)800WApplicationsTE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature9CFeaturesPC, Remote On/Off, Remote Sense, Standby OutputMounting TypeRack MountSize / Dimension9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)		AC DC Converters		
TypeFron EndNumber of Outputs6Voltage - Input180 ~ 264 VACVoltage - Output 112VVoltage - Output 212VVoltage - Output 312VVoltage - Output 412VVoltage - Output 544A, 24A, 24A, 28A, 18APower (Watts)NE (Commercial)Voltage - Isolation-Fifciency92%Operating Temperature0°C ~ 50°CFeaturesFCC, Remote On/Off, Remote Sense, Standby OutputMounting TypeAck MountSize / Dimension945" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Package	-		
Number of Outputs   6     Voltage - Input   180 ~ 264 VAC     Voltage - Output 1   12V     Voltage - Output 2   12V     Voltage - Output 3   12V     Voltage - Output 4   12V     Current - Output (Max)   24A, 24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Ack Mount     Size / Dimension   9.45° L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Series	-		
Voltage - Input   180 ~ 264 VAC     Voltage - Output 1   12V     Voltage - Output 2   12V     Voltage - Output 3   12V     Voltage - Output 4   12V     Current - Output (Max)   24A, 24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   9C< 50°C	Туре	Front End		
Notice - Output 1   12V     Voltage - Output 2   12V     Voltage - Output 3   12V     Voltage - Output 4   12V     Current - Output (Max)   24A, 24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   O°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Ack Mount     Size / Dimension   945° L x 3.94° W x 1.57° H (240.0mm x 100.0mm x 40.0mm)	Number of Outputs	6		
Voltage - Output 2   12V     Voltage - Output 3   12V     Voltage - Output 4   12V     Current - Output (Max)   24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Rack Mount     Size / Dimension   9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Voltage - Input	180 ~ 264 VAC		
Voltage - Output 3   12V     Voltage - Output 4   12V     Current - Output (Max)   24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Rack Mount     Size / Dimension   9.45" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Voltage - Output 1	12V		
Voltage - Output 4   12V     Current - Output (Max)   24A, 24A, 24A, 28A, 18A     Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Rack Mount     Size / Dimension   9.45" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Voltage - Output 2	12V		
Current - Output (Max) 24A, 24A, 24A, 28A, 18A   Power (Watts) 800W   Applications ITE (Commercial)   Voltage - Isolation -   Efficiency 92%   Operating Temperature 0°C ~ 50°C   Features PFC, Remote On/Off, Remote Sense, Standby Output   Mounting Type Rack Mount   Size / Dimension 9.45" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Voltage - Output 3	12V		
Power (Watts)   800W     Applications   ITE (Commercial)     Voltage - Isolation   -     Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Rack Mount     Size / Dimension   9.45" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Voltage - Output 4	12V		
ApplicationsITE (Commercial)Voltage - Isolation-Efficiency92%Operating Temperature0°C ~ 50°CFeaturesPFC, Remote On/Off, Remote Sense, Standby OutputMounting TypeRack MountSize / Dimension9.45" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Current - Output (Max)	24A, 24A, 24A, 24A, 28A, 18A		
Voltage - Isolation-Efficiency92%Operating Temperature0°C ~ 50°CFeaturesPFC, Remote On/Off, Remote Sense, Standby OutputMounting TypeRack MountSize / Dimension9.45" L x 3.94" W x 1.57" H (240.0mm x 40.0mm)	Power (Watts)	800W		
Efficiency   92%     Operating Temperature   0°C ~ 50°C     Features   PFC, Remote On/Off, Remote Sense, Standby Output     Mounting Type   Rack Mount     Size / Dimension   9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Applications	ITE (Commercial)		
Operating Temperature0°C ~ 50°CFeaturesPFC, Remote On/Off, Remote Sense, Standby OutputMounting TypeRack MountSize / Dimension9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Voltage - Isolation	-		
FeaturesPFC, Remote On/Off, Remote Sense, Standby OutputMounting TypeRack MountSize / Dimension9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Efficiency	92%		
Mounting Type   Rack Mount     Size / Dimension   9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 50^{\circ}\text{C}$		
Size / Dimension 9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)	Features	PFC, Remote On/Off, Remote Sense, Standby Output		
	Mounting Type	Rack Mount		
Report er	Size / Dimension	9.45" L x 3.94" W x 1.57" H (240.0mm x 100.0mm x 40.0mm)		
			Report errors?	

#### **DPS-750AB-26 C Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### DPS-750AB-26 C Payment Methods



#### **DPS-750AB-26** C Shipping Methods



If you have any question about DPS-750AB-26 C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com