

# **DPS050200U-Z5N-DF**

### DPS050200U-Z5N-DF Information

Heisener.com

Part Number DPS050200U-Z5N-DF

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 5V 10W

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **DPS050200U-Z5N-DF Specifications**

Manufacturer Part Number         DPS050200U-Z5N-DF           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         2A           Power (Watts)         10W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         65%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         2A           Power (Watts)         10W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         65%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Manufacturer Part Number	DPS050200U-Z5N-DF
AC DC Desktop, Wall Adapters  Package Series - Region Utilized North America  Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V Current - Output (Max) 2A  Power (Watts) 10W  No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial)  Efficiency Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension  AC DC Desktop, Wall Adapters  -  Acc DC Desktop, Wall Adapters  -  Acc DC Desktop, Wall Adapters  -  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  AC DC Desktop, Wall Adapters  -  Acc DC Desktop  -  Acc DC Des	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         5V           Current - Output (Max)         2A           Power (Watts)         10W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         65%           Operating Temperature         10°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2APower (Watts)10WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency65%Operating Temperature10°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 5V  Current - Output (Max) 2A  Power (Watts) 10W  No Load Power Consumption -  Polarization Negative Center Applications ITE (Commercial)  Efficiency 65%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Series	-
Input TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5\text{V}$ Current - Output (Max) $2\text{A}$ Power (Watts) $10\text{W}$ No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency $65\%$ Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.1\text{mm I.D. x } 5.5\text{mm O.D. x } 9.5\text{mm}$ Size / Dimension $2.36^{\circ}\text{ L x } 1.73^{\circ}\text{ W x } 0.98^{\circ}\text{ H } (60.0\text{mm x } 44.0\text{mm x } 25.0\text{mm})$	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  5V  Current - Output (Max)  2A  Power (Watts)  10W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Form	Wall Mount
Voltage - Output (Max) 5V  Current - Output (Max) 2A  Power (Watts) 10W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 65%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Input Type	Fixed Blade
Current - Output (Max)  Power (Watts)  10W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  65%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  10W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  65%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Voltage - Output	5V
No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  65%  Operating Temperature  10°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Current - Output (Max)	2A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency 65%  Operating Temperature 10°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Power (Watts)	10W
Applications ITE (Commercial)  Efficiency 65%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $2.36^{\circ}$ L x $1.73^{\circ}$ W x $0.98^{\circ}$ H (60.0mm x $44.0$ mm x $25.0$ mm)	No Load Power Consumption	-
Efficiency 65%  Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $2.36^{\circ}\text{L} \times 1.73^{\circ}\text{W} \times 0.98^{\circ}\text{H} (60.0\text{mm} \times 44.0\text{mm} \times 25.0\text{mm})$	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Efficiency	65%
Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)
		Report errors?

#### DPS050200U-Z5N-DF Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DPS050200U-Z5N-DF Payment Methods



















### DPS050200U-Z5N-DF Shipping Methods













If you have any question about DPS050200U-Z5N-DF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com