

Heisener.com

DPS050200UPS-P12/RP

DPS050200UPS-P12/RP Information

Part Number DPS050200UPS-P12/RP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 10W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS050200UPS-P12/RP Specifications

Manufacturer Part NumberDPS050200UPS-P12/RPManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2APower (Watts)10W
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output Current - Output (Max) Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters - Series - Voltage - Current - Output (Max)
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 2A
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 2A
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2A
Voltage - Input 90 ~ 264 VAC Voltage - Output Current - Output (Max) 90 ~ 264 VAC 2A
Voltage - Output 5V Current - Output (Max) 2A
Current - Output (Max) 2A
-
Power (Watts) 10W
No Load Power Consumption -
Polarization Positive Center
Applications ITE (Commercial)
Efficiency 65%
Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$
Output Connector Barrel Plug R/A, 0.7mm I.D. x 2.35mm O.D. x 9.5mm
Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)
Report errors's

DPS050200UPS-P12/RP Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS050200UPS-P12/RP Payment Methods



















DPS050200UPS-P12/RP Shipping Methods













If you have any question about DPS050200UPS-P12/RP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com