



DPS050280U-P14P Information

Heisener.com

Part Number DPS050280U-P14P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 14W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS050280U-P14P Specifications

Manufacturer Part Number DPS050280U-P14P Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2.8APower (Watts)14WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mmSize / Dimension-	Manufacturer Part Number	DPS050280U-P14P
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Category	Power Supplies - External/Internal (Off-Board)
Series - North America Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)2.8APower (Watts)14WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mmSize / Dimension-	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Series	-
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension Fixed Blade For a 264 VAC For a 264 VAC Set / NAC Se	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension - - - - - - - - - - - - -	Form	Wall Mount
Voltage - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Input Type	Fixed Blade
Current - Output (Max) 2.8A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Voltage - Input	90 ~ 264 VAC
Power (Watts) 14W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension 14W	Voltage - Output	5V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Current - Output (Max)	2.8A
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Power (Watts)	14W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Polarization	Positive Center
Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Efficiency	-
Size / Dimension -	Operating Temperature	-
	Output Connector	Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	-
		Report errors?

DPS050280U-P14P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS050280U-P14P Payment Methods



















DPS050280U-P14P Shipping Methods













If you have any question about DPS050280U-P14P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com