



DPS060200-P13N Information

Heisener.com

Part Number DPS060200-P13N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 6V 12W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS060200-P13N Specifications

Manufacturer Part Number DPS060200-P13N Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 6V Current - Output (Max) 2A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output6VCurrent - Output (Max)2APower (Watts)12WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Manufacturer Part Number	DPS060200-P13N
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output (Max) 2A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output6VCurrent - Output (Max)2APower (Watts)12WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output6VCurrent - Output (Max)2APower (Watts)12WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output6VCurrent - Output (Max)2APower (Watts)12WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 6V Current - Output (Max) 2A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Series	-
Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 6V Current - Output (Max) 2A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Region Utilized	North America
Voltage - Input90 ~ 132 VACVoltage - Output6VCurrent - Output (Max)2APower (Watts)12WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Form	Desktop (Class II)
Voltage - Output (Max) 2A Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Input Type	Cord
Current - Output (Max) Power (Watts) 12W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Voltage - Input	90 ~ 132 VAC
Power (Watts) 12W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Voltage - Output	6V
No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Current - Output (Max)	2A
Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Power (Watts)	12W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Polarization	Negative Center
Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Efficiency	-
Size / Dimension -	Operating Temperature	-
	Output Connector	Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm
Report errors?	Size / Dimension	-
		Report errors?

DPS060200-P13N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS060200-P13N Payment Methods





















DPS060200-P13N Shipping Methods













If you have any question about DPS060200-P13N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com