



DPS090150-P13P Information

Heisener.com

Part Number DPS090150-P13P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 9V 14W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS090150-P13P Specifications

Manufacturer Part Number DPS090150-P13P Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output9VCurrent - Output (Max)1.5APower (Watts)14WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Manufacturer Part Number	DPS090150-P13P
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output9VCurrent - Output (Max)1.5APower (Watts)14WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Category	Power Supplies - External/Internal (Off-Board)
Series - North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Poslarization Poslarization Positive Center Applications ITE (Commercial) Efficiency - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension - Orthodox (South Contest) Size / Dimension - Output Connector Size / Dime		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output9VCurrent - Output (Max)1.5APower (Watts)14WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mmSize / Dimension-	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Series	-
Input Type Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension Cord 90 ~ 132 VAC 1.5A 1.5A 1.5A 1.5A 1.5W	Region Utilized	North America
Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 90 ~ 132 VAC 9V Current - Output (Max) 1.5A Power (Watts) 14W Positive Center - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm	Form	Desktop (Class II)
Voltage - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Input Type	Cord
Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency - Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 1.5A 1.	Voltage - Input	90 ~ 132 VAC
Power (Watts) 14W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 14W	Voltage - Output	9V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Current - Output (Max)	1.5A
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Power (Watts)	14W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Polarization	Positive Center
Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension -	Efficiency	-
Size / Dimension -	Operating Temperature	-
	Output Connector	Barrel Plug, 1.7mm I.D. x 4.0mm O.D. x 9.5mm
Report errors?	Size / Dimension	-
		Report errors?

DPS090150-P13P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS090150-P13P Payment Methods





















DPS090150-P13P Shipping Methods













If you have any question about DPS090150-P13P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com