



### **DPS090150-P14N Information**

Heisener.com

Part Number DPS090150-P14N

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

AC/DC DESKTOP ADAPTER 9V 14W **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DPS090150-P14N Specifications**

Manufacturer Part Number         DPS090150-P14N           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         90 ~ 132 VAC           Voltage - Output         9V           Current - Output (Max)         1.5A           Power (Watts)         14W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm           Size / Dimension         -		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output9VCurrent - Output (Max)1.5APower (Watts)14WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mmSize / Dimension-	Manufacturer Part Number	DPS090150-P14N
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Manufacturer	CUI Inc.
Package-Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output9VCurrent - Output (Max)1.5APower (Watts)14WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mmSize / Dimension-	Category	Power Supplies - External/Internal (Off-Board)
Series - North America Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension - Possible Consumption - Polarization Agencia Sarrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input90 ~ 132 VACVoltage - Output9VCurrent - Output (Max)1.5APower (Watts)14WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mmSize / Dimension-	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 90 ~ 132 VAC Voltage - Output 9V Current - Output (Max) 1.5A Power (Watts) 14W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Series	-
Input Type  Voltage - Input  90 ~ 132 VAC  Voltage - Output  9V  Current - Output (Max)  1.5A  Power (Watts)  14W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  Cord  90 ~ 132 VAC  1.5A  1.5A  1.5A  1.5A  1.5W	Region Utilized	North America
Voltage - Input  90 ~ 132 VAC  Voltage - Output  9V  Current - Output (Max)  1.5A  Power (Watts)  14W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  90 ~ 132 VAC  9V  Current - Output (Max)  1.5A  Negative Center  - Output Connector  Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm	Form	Desktop (Class II)
Voltage - Output (Max) 1.5A  Power (Watts) 14W  No Load Power Consumption -  Polarization Negative Center Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension -	Input Type	Cord
Current - Output (Max)  1.5A  Power (Watts)  14W  No Load Power Consumption  - Polarization  Applications  ITE (Commercial)  Efficiency  - Operating Temperature  Output Connector  Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  1.5A  1.	Voltage - Input	90 ~ 132 VAC
Power (Watts)  14W  No Load Power Consumption  Polarization  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  14W  Negative Center  Negative Center	Voltage - Output	9V
No Load Power Consumption  Polarization  Negative Center  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension  -	Current - Output (Max)	1.5A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Power (Watts)	14W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Polarization	Negative Center
Operating Temperature - Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm Size / Dimension -	Applications	ITE (Commercial)
Output Connector Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm  Size / Dimension -	Efficiency	-
Size / Dimension -	Operating Temperature	-
	Output Connector	Barrel Plug, 1.7mm I.D. x 4.8mm O.D. x 9.5mm
Report errors?	Size / Dimension	-
		Report errors?

#### **DPS090150-P14N Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DPS090150-P14N Payment Methods

































If you have any question about DPS090150-P14N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com