



DPS120150U-P6P Information

Heisener.com

Part Number DPS120150U-P6P

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 12V 18W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS120150U-P6P Specifications

Manufacturer Part Number DPS120150U-P6P Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Manufacturer Part Number	DPS120150U-P6P
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, $2.5\text{mm I.D. x } 5.5\text{mm O.D. x } 12.0\text{mm}$ Size / Dimension $3.19\text{" L x } 2.09\text{" W x } 1.65\text{" H } (81.0\text{mm x } 53.0\text{mm x } 42.0\text{mm})$		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Region Utilized	North America
Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 1.5A Power (Watts) 18W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 100 ~ 240 VAC 12V 100 ~ 240 VAC 12V 100 ~ 240 VAC 100 ~ 240 VAC	Form	Wall Mount
Voltage - Output Current - Output (Max) 1.5A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 12V 1.5V 1.5A Power (Watts) 18W Positive Center Positive Center	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 18W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) 18W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Voltage - Output	12V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Current - Output (Max)	1.5A
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Power (Watts)	18W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Polarization	Positive Center
Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Efficiency	-
Size / Dimension 3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	3.19" L x 2.09" W x 1.65" H (81.0mm x 53.0mm x 42.0mm)
		Report errors?

DPS120150U-P6P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS120150U-P6P Payment Methods



















DPS120150U-P6P Shipping Methods













If you have any question about DPS120150U-P6P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com