



DPS150067U-Z6N-DF Information

Heisener.com

Part Number DPS150067U-Z6N-DF

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 15V 10W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS150067U-Z6N-DF Specifications

Manufacturer Part Number DPS150067U-Z6N-DF Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Manufacturer Part Number	DPS150067U-Z6N-DF
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)670mAPower (Watts)10WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)670mAPower (Watts)10WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Series	-
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade For C 40°C For Autor For Autor Fixed Blade Fixed Blade Fixed Blade For C 40°C For Autor For Autor	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 15V Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 90 ~ 264 VAC	Form	Wall Mount
Voltage - Output Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 15V 15V 1670mA 10W Negative Center Negative Center Negative Center 170%	Input Type	Fixed Blade
Current - Output (Max) 670mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 10W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Voltage - Output	15V
No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5 \text{mm I.D. x } 5.5 \text{mm O.D. x } 12.0 \text{mm}$ Size / Dimension 3.35 " L x 2.13 " W x 0.78 " H $(85.0 \text{mm x } 54.0 \text{mm x } 19.8 \text{mm})$	Current - Output (Max)	670mA
Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Power (Watts)	10W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	No Load Power Consumption	-
Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Efficiency	70%
Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)
		Report errors?

DPS150067U-Z6N-DF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS150067U-Z6N-DF Payment Methods



















DPS150067U-Z6N-DF Shipping Methods













If you have any question about DPS150067U-Z6N-DF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com