

Heisener.com

DPS180055UPS-P6/RN

DPS180055UPS-P6/RN Information

Part Number DPS180055UPS-P6/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 18V 10W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS180055UPS-P6/RN Specifications

Manufacturer Part Number DPS180055UPS-P6/RN Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Reckage - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Manufacturer Part Number	DPS180055UPS-P6/RN
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Series	-
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Form	Wall Mount
Voltage - Output Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 18V 18V 18V 18V 190 190 190 100 100 100 100 10	Input Type	Fixed Blade
Current - Output (Max) 550mA Power (Watts) 9.9W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 9.9W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 10°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Voltage - Output	18V
No Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 65% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 12.5\text{mm}$ Size / Dimension 2.36 " L $x 1.73$ " W $x 0.98$ " H (60.0mm $x 44.0\text{mm}$ $x 25.0\text{mm}$)	Current - Output (Max)	550mA
PolarizationNegative CenterApplicationsITE (Commercial)Efficiency 65% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 12.5\text{mm}$ Size / Dimension 2.36 " L $x 1.73$ " W $x 0.98$ " H (60.0mm $x 44.0\text{mm}$ $x 25.0\text{mm}$)	Power (Watts)	9.9W
Applications ITE (Commercial) Efficiency 65% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension $2.36^{\circ}\text{L x } 1.73^{\circ}\text{W x } 0.98^{\circ}\text{H } (60.0\text{mm x } 44.0\text{mm x } 25.0\text{mm})$	No Load Power Consumption	-
Efficiency 65% Operating Temperature $10^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension $2.36^{\circ}\text{L} \times 1.73^{\circ}\text{W} \times 0.98^{\circ}\text{H} (60.0\text{mm} \times 44.0\text{mm} \times 25.0\text{mm})$	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Efficiency	65%
Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Operating Temperature	10°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 12.5mm
Report errors?	Size / Dimension	2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)
		Report errors?

DPS180055UPS-P6/RN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS180055UPS-P6/RN Payment Methods



















DPS180055UPS-P6/RN Shipping Methods













If you have any question about DPS180055UPS-P6/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com