



DPS240042U-Z6P-DF Information

Heisener.com

Part Number DPS240042U-Z6P-DF

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 24V 10W

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPS240042U-Z6P-DF Specifications

Manufacturer Part Number DPS240042U-Z6P-DF Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Manufacturer Part Number	DPS240042U-Z6P-DF
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Manufacturer	CUI Inc.
Package - Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)420mAPower (Watts)10WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mmSize / Dimension3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Package	-
Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Series	-
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 90 ~ 264 VAC	Form	Wall Mount
Voltage - Output Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Input Type	Fixed Blade
Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 10W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Voltage - Output	24V
No Load Power Consumption - Positive Center Applications ITE (Commercial) Efficiency	Current - Output (Max)	420mA
Polarization Positive Center Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Power (Watts)	10W
Applications ITE (Commercial) Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	No Load Power Consumption	-
Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Efficiency	70%
Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 12.0mm
Report errors?	Size / Dimension	3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)
		Report errors?

DPS240042U-Z6P-DF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPS240042U-Z6P-DF Payment Methods





















DPS240042U-Z6P-DF Shipping Methods













If you have any question about DPS240042U-Z6P-DF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com