



### DPS240042U-Z7N-DF Information

Heisener.com

Part Number DPS240042U-Z7N-DF

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 24V 10W

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DPS240042U-Z7N-DF Specifications

Manufacturer Part Number         DPS240042U-Z7N-DF           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         420mA           Power (Watts)         10W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         420mA           Power (Watts)         10W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Manufacturer Part Number	DPS240042U-Z7N-DF
AC DC Desktop, Wall Adapters  Package Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC  Voltage - Output Current - Output (Max) 10W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension  AC DC Desktop, Wall Adapters  - AC DC Desktop, Wall Adapters - AC DC Desktop, Wall Adapters  - AC DC Desktop  - AC DC	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         420mA           Power (Watts)         10W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         70%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)420mAPower (Watts)10WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency70%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 420mA Power (Watts) 10W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency 70% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 420mA  Power (Watts) 10W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Series	-
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 420mA  Power (Watts) 10W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  24V  Current - Output (Max)  Power (Watts)  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  90 ~ 264 VAC	Form	Wall Mount
Voltage - Output  Current - Output (Max)  420mA  Power (Watts)  10W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Input Type	Fixed Blade
Current - Output (Max) 420mA  Power (Watts) 10W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  10W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  70%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Voltage - Output	24V
No Load Power Consumption - Polarization Negative Center   Applications ITE (Commercial)   Efficiency 70%   Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm   Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Current - Output (Max)	420mA
Polarization Negative Center  Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension $3.35^{\circ}\text{L} \times 2.13^{\circ}\text{W} \times 0.78^{\circ}\text{H} (85.0\text{mm} \times 54.0\text{mm} \times 19.8\text{mm})$	Power (Watts)	10W
Applications ITE (Commercial)  Efficiency 70%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	No Load Power Consumption	-
Efficiency 70%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Polarization	Negative Center
	Applications	ITE (Commercial)
Output Connector  Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Efficiency	70%
Size / Dimension 3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Barrel Plug, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
Report errors?	Size / Dimension	3.35" L x 2.13" W x 0.78" H (85.0mm x 54.0mm x 19.8mm)
		Report errors?

### **DPS240042U-Z7N-DF Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DPS240042U-Z7N-DF Payment Methods





















## DPS240042U-Z7N-DF Shipping Methods













If you have any question about DPS240042U-Z7N-DF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com