

# DPS240050UPS-P5P-SZ

### DPS240050UPS-P5P-SZ Information



For Reference Only

Part Number DPS240050UPS-P5P-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 24V 12W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DPS240050UPS-P5P-SZ Specifications

Manufacturer Part Number         DPS240050UPS-P5P-SZ           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         500mA           Power (Watts)         12W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         65%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         500mA           Power (Watts)         12W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         65%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Manufacturer Part Number	DPS240050UPS-P5P-SZ
AC DC Desktop, Wall Adapters  Package Series - Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC  Voltage - Output Current - Output (Max) 12W No Load Power (Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O"C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension  AC DC Desktop, Wall Adapters  - AC DC Desktop, Wall Adapters - Commercial Polarization Positive Center Applications Size / Dimension  AC DC Desktop, Wall Adapters  - Commercial Positive Genter  - Commercial	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         90 ~ 264 VAC           Voltage - Output         24V           Current - Output (Max)         500mA           Power (Watts)         12W           No Load Power Consumption         -           Polarization         Positive Center           Applications         ITE (Commercial)           Efficiency         65%           Operating Temperature         0°C ~ 40°C           Output Connector         Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)500mAPower (Watts)12WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency65%Operating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 500mA Power (Watts) 12W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 65% Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 500mA  Power (Watts) 12W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency 65%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 244 VAC	Series	-
Input Type Fixed Blade  Voltage - Input 90 ~ 264 VAC  Voltage - Output 24V  Current - Output (Max) 500mA  Power (Watts) 12W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency 65%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  24V  Current - Output (Max)  500mA  Power (Watts)  12W  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  90 ~ 264 VAC	Form	Wall Mount
Voltage - Output  Current - Output (Max)  500mA  Power (Watts)  12W  No Load Power Consumption  Polarization  Polarization  Applications  ITE (Commercial)  Efficiency  65%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Input Type	Fixed Blade
Current - Output (Max) 500mA  Power (Watts) 12W  No Load Power Consumption -  Polarization Positive Center  Applications ITE (Commercial)  Efficiency 65%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  12W  No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  65%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Voltage - Output	24V
No Load Power Consumption  Polarization  Positive Center  Applications  ITE (Commercial)  Efficiency  65%  Operating Temperature  0°C ~ 40°C  Output Connector  Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Current - Output (Max)	500mA
Polarization Positive Center  Applications ITE (Commercial)  Efficiency 65%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Power (Watts)	12W
Applications ITE (Commercial)  Efficiency 65%  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	No Load Power Consumption	-
Efficiency 65%  Operating Temperature 0°C ~ 40°C  Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Efficiency	65%
Size / Dimension 2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	2.36" L x 1.73" W x 0.98" H (60.0mm x 44.0mm x 25.0mm)
		Report errors?

### DPS240050UPS-P5P-SZ Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## DPS240050UPS-P5P-SZ Payment Methods



















## DPS240050UPS-P5P-SZ Shipping Methods













If you have any question about DPS240050UPS-P5P-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com