



DPX6024S05 Information



For Reference Only

Part Number DPX6024S05

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description CONV DC/DC SGL 5V 12A OUT 60W

Package Modul

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DPX6024S05 Specifications

Manufacturer Part Number DPX6024S05 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series DPX Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	•	
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series DPX Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Manufacturer Part Number	DPX6024S05
Package Module Series DPX Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Manufacturer	TDK-Lambda Americas Inc.
Package Module Series DPX Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series DPX Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Package	Module
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Series	DPX
Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Туре	Isolated
Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Voltage - Input (Min)	18V
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Voltage - Input (Max)	36V
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 12A Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension -40°C ~ 85°C W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	_	-
Current - Output (Max) Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 12A 60W DIV (Commercial) -40°C ~ 85°C 85% Mounting Type DIV (Commercial) 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)		-
Power (Watts) 60W Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Current - Output (Max)	12A
Operating Temperature -40°C ~ 85°C Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Power (Watts)	60W
Efficiency 85% Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Applications	ITE (Commercial)
Mounting Type DIN Rail Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Module Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Efficiency	85%
Size / Dimension 4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)	Mounting Type	
	Package / Case	Module
Report errors?	Size / Dimension	4.92" L x 0.96" W x 2.27" H (125.0mm x 24.5mm x 57.6mm)
		Report errors?

DPX6024S05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DPX6024S05 Payment Methods



















DPX6024S05 Shipping Methods













If you have any question about DPX6024S05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com