

DR125-472-R Information

Heisener.com

Part Number DR125-472-R

Manufacturer Eaton

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 4.72MH 268MA 7.53 OHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DR125-472-R Specifications

Manufacturer Eaton Category Inductors, Coils, Chokes Package Nonstandard Series DR Type Wirewound Material - Core Ferrite Inductance 4,72mH Tolerance ±20% Current Rating 268mA Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Manufacturer Part Number	DR125-472-R
Fixed Inductors Package Nonstandard Series DR Type Wirewound Material - Core Ferrite Inductance 4.72mH Tolerance ±20% Current Rating 268mA Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Manufacturer	Eaton
PackageNonstandardSeriesDRTypeWirewoundMaterial - CoreFerriteInductance4.72mHTolerance±20%Current Rating268mACurrent - Saturation320mAShieldingShieldedDC Resistance (DCR)7.53 OhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Category	Inductors, Coils, Chokes
Series DR Type Wirewound Material - Core Ferrite Inductance 4.72mH Tolerance ±20% Current Rating 268mA Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -		Fixed Inductors
TypeWirewoundMaterial - CoreFerriteInductance4.72mHTolerance±20%Current Rating268mACurrent - Saturation320mAShieldingShieldedDC Resistance (DCR)7.53 OhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Package	Nonstandard
Material - Core Ferrite Inductance 4.72mH Tolerance ±20% Current Rating 268mA Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Series	DR
Inductance 4.72mH Tolerance ±20% Current Rating 268mA Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Туре	Wirewound
Tolerance ±20% Current Rating 268mA Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature 40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Material - Core	Ferrite
Current Rating Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Inductance	4.72mH
Current - Saturation 320mA Shielding Shielded DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Tolerance	±20%
Shielding DC Resistance (DCR) 7.53 Ohm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current Rating	268mA
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Supplier Device Package - 7.53 Ohm 7.53 Ohm - 0. Supplier Device Package - 7.53 Ohm - 8.53 Ohm - 8.54 Ohm - 8.55 Ohm	Current - Saturation	320mA
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Shielding	Shielded
Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	DC Resistance (DCR)	7.53 Ohm
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Q @ Freq	-
Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Self Resonant	-
Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Test	100kHz
Package / Case Nonstandard Supplier Device Package -	Features	-
Supplier Device Package -	Mounting Type	Surface Mount
	Package / Case	Nonstandard
Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Supplier Device Package	-
	Size / Dimension	0.492" L x 0.492" W (12.50mm x 12.50mm)

Height - Seated (Max) 0.236" (6.00mm) Report errors?

DR125-472-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DR125-472-R Payment Methods



















DR125-472-R Shipping Methods













If you have any question about DR125-472-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com