

DR73-151-R Information



For Reference Only

Part Number DR73-151-R

Manufacturer Eaton

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 150UH 580MA 851 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DR73-151-R Specifications

Manufacturer Eaton Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series DR Type Wirewound Material - Core Ferrite Inductance 150µH Tolerance ±20% Current Rating 580mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Manufacturer Part Number	DR73-151-R
Fixed Inductors	Manufacturer	Eaton
PackageNonstandardSeriesDRTypeWirewoundMaterial - CoreFerriteInductance150μHTolerance±20%Current Rating580mACurrent - Saturation650mAShieldingShieldedDC Resistance (DCR)851 mOhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandard	Category	Inductors, Coils, Chokes
Series DR Type Wirewound Material - Core Ferrite Inductance 150μH Tolerance ±20% Current Rating 580mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard		Fixed Inductors
Type Wirewound Material - Core Ferrite Inductance $150\mu H$ Tolerance $\pm 20\%$ Current Rating $580mA$ Current - Saturation $650mA$ Shielding Shielded DC Resistance (DCR) $851 mOhm$ Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Frequency - Test $100kHz$ Features - Mounting Type Surface Mount Package / Case Nonstandard	Package	Nonstandard
Material - Core Ferrite Inductance 150μH Tolerance $\pm 20\%$ Current Rating 580mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard	Series	DR
Inductance 150μH Tolerance ±20% Current Rating 580mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Туре	Wirewound
Tolerance ±20% Current Rating 580mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Material - Core	Ferrite
Current Rating 580mA Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Inductance	150μΗ
Current - Saturation 650mA Shielding Shielded DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Tolerance	±20%
Shielding DC Resistance (DCR) 851 mOhm Q @ Freq - Frequency - Self Resonant Ratings Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard	Current Rating	580mA
DC Resistance (DCR) Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test Frequency - Test Features - Mounting Type Surface Mount Package / Case 851 mOhm - 852 moh - 853 moh - 853 moh - 854 moh - 855 moh - 855 moh - 857 moh - 857 moh - 858 moh -	Current - Saturation	650mA
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Shielding	Shielded
Frequency - Self Resonant Ratings Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard	DC Resistance (DCR)	851 mOhm
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Q @ Freq	-
Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Frequency - Self Resonant	-
Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard	Frequency - Test	100kHz
Package / Case Nonstandard	Features	-
	Mounting Type	Surface Mount
Supplier Device Package -	Package / Case	Nonstandard
	Supplier Device Package	-
Size / Dimension 0.299" L x 0.299" W (7.60mm x 7.60mm)	Size / Dimension	0.299" L x 0.299" W (7.60mm x 7.60mm)

Height - Seated (Max)	0.140" (3.55mm)
	Report errors?

DR73-151-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DR73-151-R Payment Methods





















DR73-151-R Shipping Methods













If you have any question about DR73-151-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com