

DR73-820-R Information



For Reference Only

Part Number DR73-820-R

Manufacturer Eaton

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 82UH 860MA 384 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DR73-820-R Specifications

Manufacturer Eaton Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series DR Type Wirewound Material - Core Ferrite Inductance 82µH Tolerance ±20% Current Rating 860mA Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Size / Dimension 0.299" L x 0.299" W (7.60mm x 7.60mm)	Manufacturer Part Number	DR73-820-R
Fixed Inductors Package Nonstandard Series DR Type Wirewound Material - Core Ferrite Inductance 82µH Tolerance ±20% Current Rating 860mA Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Manufacturer	Eaton
Package Nonstandard Series DR Type Wirewound Material - Core Ferrite Inductance 82µH Tolerance ±20% Current Rating 860mA Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Category	Inductors, Coils, Chokes
Series DR Type Wirewound Material - Core Ferrite Inductance 82μH Tolerance ±20% Current Rating 860mA Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -		Fixed Inductors
TypeWirewoundMaterial - CoreFerriteInductance82μHTolerance±20%Current Rating860mACurrent - Saturation890mAShieldingShieldedDC Resistance (DCR)384 mOhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Package	Nonstandard
Material - Core Ferrite Inductance 82μH Tolerance ±20% Current Rating 860mA Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Series	DR
Inductance82μHTolerance±20%Current Rating860mACurrent - Saturation890mAShieldingShieldedDC Resistance (DCR)384 mOhmQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-40°C ~ 125°CFrequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Туре	Wirewound
Tolerance ±20% Current Rating 860mA Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Material - Core	Ferrite
Current Rating Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Inductance	82μΗ
Current - Saturation 890mA Shielding Shielded DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Tolerance	±20%
Shielding DC Resistance (DCR) 384 mOhm Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current Rating	860mA
DC Resistance (DCR) Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current - Saturation	890mA
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Shielding	Shielded
Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	DC Resistance (DCR)	384 mOhm
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Q @ Freq	-
Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Self Resonant	-
Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Test	100kHz
Package / Case Nonstandard Supplier Device Package -	Features	-
Supplier Device Package -	Mounting Type	Surface Mount
	Package / Case	Nonstandard
Size / Dimension 0.299" L x 0.299" W (7.60mm x 7.60mm)	Supplier Device Package	-
0.222 2.1. (1.00mm. 1.100mm)	Size / Dimension	0.299" L x 0.299" W (7.60mm x 7.60mm)

Height - Seated (Max)	0.140" (3.55mm)
	Report errors?

DR73-820-R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DR73-820-R Payment Methods





















DR73-820-R Shipping Methods











If you have any question about DR73-820-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com