



## **DS1100SDC-3 Information**

Heisener.com

Part Number DS1100SDC-3

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** 48-V DC INPT 12V OUTPT 1100W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DS1100SDC-3 Specifications**

Manufacturer Part Number         DS1100SDC-3           Manufacturer         Artesyn Embedded Technologies           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         DS1100SDC           Type         Front End           Voltage - Input (Min)         -36V           Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)			
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         DS 1100SDC           Type         Front End           Voltage - Input (Min)         -36V           Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Manufacturer Part Number	DS1100SDC-3	
Package         -           Series         DS1100SDC           Type         Front End           Voltage - Input (Min)         -36V           Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Manufacturer	Artesyn Embedded Technologies	
Package         -           Series         DS1100SDC           Type         Front End           Voltage - Input (Min)         -36V           Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         DS1100SDC           Type         Front End           Voltage - Input (Min)         -36V           Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)		DC DC Converters	
Type         Front End           Voltage - Input (Min)         -36V           Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Package	-	
Voltage - Input (Min)       -36V         Voltage - Input (Max)       -72V         Number of Outputs       1         Voltage - Output 1       12V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       91.76A         Power (Watts)       1100W         Applications       ITE (Commercial)         Operating Temperature       0°C ~ 40°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Series	DS1100SDC	
Voltage - Input (Max)         -72V           Number of Outputs         1           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         91.76A           Power (Watts)         1100W           Applications         ITE (Commercial)           Operating Temperature         0°C ~ 40°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Туре	Front End	
Number of Outputs       1         Voltage - Output 1       12V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       91.76A         Power (Watts)       1100W         Applications       ITE (Commercial)         Operating Temperature       0°C ~ 40°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Voltage - Input (Min)	-36V	
Voltage - Output 1       12V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       91.76A         Power (Watts)       1100W         Applications       ITE (Commercial)         Operating Temperature       0°C ~ 40°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Voltage - Input (Max)	-72V	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  O°C ~ 40°C  Efficiency  Mounting Type  Rack Mount  Package / Case  Size / Dimension  -  Voltage - Output 3  -  Current - Output (Max)  91.76A  -  1100W  1100W  91.76A  91.76A	Number of Outputs	1	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  O°C ~ 40°C  Efficiency  90%  Mounting Type  Rack Mount  Package / Case  - Size / Dimension  -  Voltage - Output 3  -  Rack Mount  -  7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Voltage - Output 1	12V	
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  0°C ~ 40°C  Efficiency  90%  Mounting Type  Rack Mount  Package / Case  -  Size / Dimension  -  1.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Voltage - Output 2	-	
Current - Output (Max) 91.76A  Power (Watts) 1100W  Applications ITE (Commercial)  Operating Temperature 0°C ~ 40°C  Efficiency 90%  Mounting Type Rack Mount  Package / Case -  Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Voltage - Output 3	-	
Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  0°C ~ 40°C  Efficiency  90%  Mounting Type  Rack Mount  Package / Case  5ize / Dimension  1100W  Applications  ITE (Commercial)  0°C ~ 40°C  Rack Mount  90%  Rack Mount  1100W  1100W	Voltage - Output 4	-	
Applications ITE (Commercial)  Operating Temperature 0°C ~ 40°C  Efficiency 90%  Mounting Type Rack Mount  Package / Case -  Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Current - Output (Max)	91.76A	
Operating Temperature 0°C ~ 40°C  Efficiency 90%  Mounting Type Rack Mount  Package / Case -  Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Power (Watts)	1100W	
Efficiency 90%  Mounting Type Rack Mount  Package / Case -  Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Applications	ITE (Commercial)	
Mounting Type Rack Mount  Package / Case - Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Operating Temperature	0°C ~ 40°C	
Package / Case - Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Efficiency	90%	
Size / Dimension 7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	Mounting Type	Rack Mount	
	Package / Case	-	
Report errors?	Size / Dimension	7.74" L x 3.40" W x 1.52" H (196.5mm x 86.3mm x 38.5mm)	
		Report error	s?

### **DS1100SDC-3 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **DS1100SDC-3 Payment Methods**



















## **DS1100SDC-3 Shipping Methods**













If you have any question about DS1100SDC-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com