

DS1230AB-100 Information



For Reference Only

Part Number DS1230AB-100

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)

Memory

Description IC NVSRAM 256KBIT 100NS 28EDIP **Package** 28-DIP Module (0.600", 15.24mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DS1230AB-100 Specifications

Manufacturer Part Number DS1230AB-100 Manufacturer Maxim Integrated Category Integrated Circuits (ICs) Memory Memory Package 28-DIP Module (0.600", 15.24mm) Series - Memory Type Non-Volatile Memory Format NVSRAM Technology NVSRAM (Non-Volatile SRAM) Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP		
Category Integrated Circuits (ICs) Memory Package 28-DIP Module (0.600", 15.24mm) Series - Memory Type Non-Volatile Memory Format NVSRAM Technology NVSRAM (Non-Volatile SRAM) Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP	Manufacturer Part Number	DS1230AB-100
Memory Package 28-DIP Module (0.600", 15.24mm) Series - Memory Type Non-Volatile Memory Format NVSRAM Technology NVSRAM (Non-Volatile SRAM) Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP	Manufacturer	Maxim Integrated
Package 28-DIP Module (0.600", 15.24mm) Series - Memory Type Non-Volatile Memory Format NVSRAM Technology NVSRAM (Non-Volatile SRAM) Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP	Category	Integrated Circuits (ICs)
Series - Memory Type Non-Volatile Memory Format NVSRAM Technology NVSRAM (Non-Volatile SRAM) Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency - Clock Frequency Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP		Memory
Memory TypeNon-VolatileMemory FormatNVSRAMTechnologyNVSRAM (Non-Volatile SRAM)Memory Size256Kb (32K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page100nsAccess Time100nsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / Case28-DIP Module (0.600", 15.24mm)Supplier Device Package28-EDIP	Package	28-DIP Module (0.600", 15.24mm)
Memory FormatNVSRAMTechnologyNVSRAM (Non-Volatile SRAM)Memory Size256Kb (32K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page100nsAccess Time100nsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / Case28-DIP Module (0.600", 15.24mm)Supplier Device Package28-EDIP	Series	-
Technology NVSRAM (Non-Volatile SRAM) Memory Size 256Kb (32K x 8) Memory Interface Parallel Clock Frequency Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply Operating Temperature Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package	Memory Type	Non-Volatile
Memory Size256Kb (32K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page100nsAccess Time100nsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / Case28-DIP Module (0.600", 15.24mm)Supplier Device Package28-EDIP	Memory Format	NVSRAM
Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page100nsAccess Time100nsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / Case28-DIP Module (0.600", 15.24mm)Supplier Device Package28-EDIP	Technology	NVSRAM (Non-Volatile SRAM)
Clock Frequency Write Cycle Time - Word, Page 100ns Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package	Memory Size	256Kb (32K x 8)
Write Cycle Time - Word, Page Access Time 100ns Voltage - Supply 4.75 V ~ 5.25 V Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package	Memory Interface	Parallel
Access Time $100ns$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (TA)Mounting TypeThrough HolePackage / Case 28-DIP Module $(0.600", 15.24\text{mm})$ Supplier Device Package 28-EDIP	Clock Frequency	-
Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (TA) Mounting Type Through Hole Package / Case 28-DIP Module $(0.600^{\circ}, 15.24\text{mm})$ Supplier Device Package 28-EDIP	Write Cycle Time - Word, Page	100ns
Operating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / Case28-DIP Module (0.600", 15.24mm)Supplier Device Package28-EDIP	Access Time	100ns
Mounting Type Through Hole Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP	Voltage - Supply	4.75 V ~ 5.25 V
Package / Case 28-DIP Module (0.600", 15.24mm) Supplier Device Package 28-EDIP	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C} \text{ (TA)}$
Supplier Device Package 28-EDIP	Mounting Type	Through Hole
	Package / Case	28-DIP Module (0.600", 15.24mm)
	Supplier Device Package	28-EDIP
Report errors?		Report errors?

DS1230AB-100 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DS1230AB-100 Payment Methods



















DS1230AB-100 Shipping Methods













If you have any question about DS1230AB-100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com