



DS2400618000G Information

Heisener.com

Part Number DS2400618000G Manufacturer Amphenol Anytek

Category Connectors, Interconnects Terminal Blocks - Specialized

Description TERM BLK MIDDLE 6POS 25.0MM GRAY

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DS2400618000G Specifications

Manufacturer DS2400618000G Manufacturer Amphenol Anytek Category Connectors, Interconnects Terminal Blocks - Specialized Package - Series DS Type Middle Mounting Type Direct Mount Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin Housing Colors Gray		
Category Connectors, Interconnects Terminal Blocks - Specialized Package - Series DS Type Middle Mounting Type Direct Mount Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Manufacturer Part Number	DS2400618000G
Package - Series DS Type Middle Mounting Type Direct Mount Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Manufacturer	Amphenol Anytek
Package-SeriesDSTypeMiddleMounting TypeDirect MountNumber of Positions6Number of Levels1Terminal - Width25.0mmTermination StyleSpring CageCurrent - IEC18AVoltage - IEC400VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG16-28 AWGWire Gauge or Range - mm²0.08-1.5mm²FeaturesEngagement Pin	Category	Connectors, Interconnects
Series DS Type Middle Mounting Type Direct Mount Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin		Terminal Blocks - Specialized
Type Middle Mounting Type Direct Mount Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Package	-
Mounting Type Direct Mount Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Series	DS
Number of Positions 6 Number of Levels 1 Terminal - Width 25.0mm Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Engagement Pin	Туре	Middle
Number of Levels1Terminal - Width25.0mmTermination StyleSpring CageCurrent - IEC18AVoltage - IEC400VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG16-28 AWGWire Gauge or Range - mm²0.08-1.5mm²FeaturesEngagement Pin	Mounting Type	Direct Mount
Terminal - Width Termination Style Spring Cage Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features 25.0mm 25.0mm Annual Cage Spring Cage 18A 10A 400V 10A 10A 10A 10A 16-28 AWG Engagement Pin	Number of Positions	6
Termination Style Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Number of Levels	1
Current - IEC 18A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Terminal - Width	25.0mm
Voltage - IEC400VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG16-28 AWGWire Gauge or Range - mm²0.08-1.5mm²FeaturesEngagement Pin	Termination Style	Spring Cage
Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 16-28 AWG Wire Gauge or Range - mm² 0.08-1.5mm² Features Engagement Pin	Current - IEC	18A
Voltage - UL300VWire Gauge or Range - AWG16-28 AWGWire Gauge or Range - mm²0.08-1.5mm²FeaturesEngagement Pin	Voltage - IEC	400V
Wire Gauge or Range - AWG Wire Gauge or Range - mm ² Features 16-28 AWG 0.08-1.5mm ² Engagement Pin	Current - UL	10A
Wire Gauge or Range - mm ² Features 0.08-1.5mm ² Engagement Pin	Voltage - UL	300V
Features Engagement Pin	Wire Gauge or Range - AWG	16-28 AWG
	Wire Gauge or Range - mm ²	0.08-1.5mm ²
Housing Color Gray	Features	Engagement Pin
Housing Color Gray	Housing Color	Gray
Report errors?		Report errors?

DS2400618000G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DS2400618000G Payment Methods



















DS2400618000G Shipping Methods













If you have any question about DS2400618000G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com