



### **DS460SDC-3 Information**

Heisener.com

Part Number DS460SDC-3

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

**Description** PWR SUP 12V 460W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DS460SDC-3 Specifications**

Manufacturer Part Number         DS460SDC-3           Manufacturer         Artesyn Embedded Technologies           Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         DS460SDC-3           Type         Front End           Voltage - Input (Min)         40V           Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)		
Category         Power Supplies - External/Internal (Off-Board)           DC DC Converters           Package         -           Series         DS460SDC-3           Type         Front End           Voltage - Input (Min)         40V           Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Manufacturer Part Number	DS460SDC-3
Package         -           Series         DS460SDC-3           Type         Front End           Voltage - Input (Min)         40V           Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Manufacturer	Artesyn Embedded Technologies
Package         -           Series         DS460SDC-3           Type         Front End           Voltage - Input (Min)         40V           Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         DS460SDC-3           Type         Front End           Voltage - Input (Min)         40V           Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)		DC DC Converters
Type         Front End           Voltage - Input (Min)         40V           Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Package	-
Voltage - Input (Min)       40V         Voltage - Input (Max)       72V         Number of Outputs       1         Voltage - Output 1       12.3V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       36A         Power (Watts)       460W         Applications       ITE (Commercial)         Operating Temperature       -10°C ~ 50°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Series	DS460SDC-3
Voltage - Input (Max)         72V           Number of Outputs         1           Voltage - Output 1         12.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         36A           Power (Watts)         460W           Applications         ITE (Commercial)           Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Type	Front End
Number of Outputs       1         Voltage - Output 1       12.3V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       36A         Power (Watts)       460W         Applications       ITE (Commercial)         Operating Temperature       -10°C ~ 50°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Voltage - Input (Min)	40V
Voltage - Output 1       12.3V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       36A         Power (Watts)       460W         Applications       ITE (Commercial)         Operating Temperature       -10°C ~ 50°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Voltage - Input (Max)	72V
Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       36A         Power (Watts)       460W         Applications       ITE (Commercial)         Operating Temperature       -10°C ~ 50°C         Efficiency       90%         Mounting Type       Rack Mount         Package / Case       -         Size / Dimension       9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Number of Outputs	1
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  Operating Temperature  Efficiency  Mounting Type  Rack Mount  Package / Case  Size / Dimension  - Current - Output (Max)  36A	Voltage - Output 1	12.3V
Voltage - Output 4  Current - Output (Max)  36A  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -10°C ~ 50°C  Efficiency  90%  Mounting Type  Rack Mount  Package / Case  Size / Dimension	Voltage - Output 2	-
Current - Output (Max)  36A  Power (Watts)  Applications  ITE (Commercial)  Operating Temperature  -10°C ~ 50°C  Efficiency  90%  Mounting Type  Rack Mount  Package / Case  -  Size / Dimension  36A  460W  Applications  ITE (Commercial)  -10°C ~ 50°C  -10	Voltage - Output 3	-
Power (Watts)460WApplicationsITE (Commercial)Operating Temperature-10°C ~ 50°CEfficiency90%Mounting TypeRack MountPackage / Case-Size / Dimension9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Operating Temperature -10°C ~ 50°C  Efficiency 90%  Mounting Type Rack Mount  Package / Case -  Size / Dimension 9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Current - Output (Max)	36A
Operating Temperature         -10°C ~ 50°C           Efficiency         90%           Mounting Type         Rack Mount           Package / Case         -           Size / Dimension         9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Power (Watts)	460W
Efficiency 90%  Mounting Type Rack Mount  Package / Case -  Size / Dimension 9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Applications	ITE (Commercial)
Mounting Type Rack Mount  Package / Case - Size / Dimension 9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Operating Temperature	-10°C ~ 50°C
Package / Case - Size / Dimension 9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Efficiency	90%
Size / Dimension 9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)	Mounting Type	Rack Mount
	Package / Case	-
Report errors?	Size / Dimension	9.57" L x 3.40" W x 1.57" H (243.2mm x 86.4mm x 39.9mm)
		Report errors?

### **DS460SDC-3 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **DS460SDC-3 Payment Methods**



















# **DS460SDC-3 Shipping Methods**













If you have any question about DS460SDC-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com