



DSC2011FL1-E0002 Information

Heisener.com

Part Number DSC2011FL1-E0002 Manufacturer Microchip Technology

Category Crystals, Oscillators, Resonators

Pin Configurable/Selectable Oscillators

Description OSC MEMS CONFIGURABLE OUTPUT

14-SMD, No Lead **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DSC2011FL1-E0002 Specifications

Manufacturer Part Number DSC2011FL1-E0002 Manufacturer Microchip Technology Category Crystals, Oscillators, Resonators Package 14-SMD, No Lead Series DSC2011 Type MEMS (Silicon) Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead		
Category Crystals, Oscillators, Resonators Pin Configurable/Selectable Oscillators Package 14-SMD, No Lead Series DSC2011 Type MEMS (Silicon) Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Manufacturer Part Number	DSC2011FL1-E0002
Package 14-SMD, No Lead Series DSC2011 Type MEMS (Silicon) Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Manufacturer	Microchip Technology
Package 14-SMD, No Lead Series DSC2011 Type MEMS (Silicon) Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series DSC2011 Type MEMS (Silicon) Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead		Pin Configurable/Selectable Oscillators
Type MEMS (Silicon) Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Package	14-SMD, No Lead
Frequency - Output 1 100MHz, 106.25MHz, 125MHz, 156.25MHz Frequency - Output 2 25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Series	DSC2011
Frequency - Output 2 25 MHz, 50 MHz, 100 MHz, 125 MHz, 156.25 MHz Function $Enable/Disable$ Output $LVCMOS$ Voltage - Supply $2.25 \text{ V} \sim 3.6 \text{ V}$ Frequency Stability ± 50 ppm Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Current - Supply (Max) 32 mA (Typ) Size / Dimension $0.126'' \text{ L} \times 0.098'' \text{ W} (3.20 \text{mm} \times 2.50 \text{mm})$ Height $0.035'' (0.90 \text{mm})$ Package / Case $14-S$ MD, No Lead	Туре	MEMS (Silicon)
Function Enable/Disable Output LVCMOS Voltage - Supply 2.25 V ~ 3.6 V Frequency Stability ±50ppm Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Frequency - Output 1	100MHz, 106.25MHz, 125MHz, 156.25MHz
OutputLVCMOSVoltage - Supply $2.25 \text{ V} \sim 3.6 \text{ V}$ Frequency Stability $\pm 50\text{ppm}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Current - Supply (Max) 32mA (Typ)Size / Dimension $0.126^{\circ}\text{ L} \times 0.098^{\circ}\text{ W} (3.20\text{mm} \times 2.50\text{mm})$ Height 0.035° (0.90mm)Package / Case 14-SMD , No Lead	Frequency - Output 2	25MHz, 50MHz, 100MHz, 125MHz, 156.25MHz
Voltage - Supply $2.25 \text{ V} \sim 3.6 \text{ V}$ Frequency Stability $\pm 50 \text{ppm}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Current - Supply (Max) 32mA (Typ) Size / Dimension $0.126^{\circ}\text{L x } 0.098^{\circ}\text{W } (3.20 \text{mm x } 2.50 \text{mm})$ Height $0.035^{\circ} (0.90 \text{mm})$ Package / Case 14-SMD, No Lead	Function	Enable/Disable
Frequency Stability $\pm 50 \text{ppm}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Current - Supply (Max) 32mA (Typ) Size / Dimension $0.126^{\circ}\text{L} \times 0.098^{\circ}\text{W}$ (3.20mm x 2.50mm) Height 0.035° (0.90mm) Package / Case 14-SMD , No Lead	Output	LVCMOS
Operating Temperature -40°C ~ 105°C Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Voltage - Supply	2.25 V ~ 3.6 V
Current - Supply (Max) 32mA (Typ) Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Frequency Stability	±50ppm
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Operating Temperature	-40°C ~ 105°C
Height 0.035" (0.90mm) Package / Case 14-SMD, No Lead	Current - Supply (Max)	32mA (Typ)
Package / Case 14-SMD, No Lead	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
	Height	0.035" (0.90mm)
Report errors?	Package / Case	14-SMD, No Lead
		Report errors?

DSC2011FL1-E0002 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DSC2011FL1-E0002 Payment Methods



















DSC2011FL1-E0002 Shipping Methods













If you have any question about DSC2011FL1-E0002, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com