

## **DSEE55-24N1F**

lest a Quote

### **DSEE55-24N1F Information**

Heisener.com	Part Number	DSEE55-24N1F	
	Manufacturer	IXYS	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
	Description	DIODE ARRAY GP 1200V 60A I4PAC	
	Package	i4-Pac?-3	
		For the pricing/inventory/lead time, please contact	
		us Walation https://www.lationana.com	Ι.
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **DSEE55-24N1F** Specifications

Diodes - Rectifiers - ArraysPackagei4-Pac?-3SeriesHiPerRED?Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?		
CategoryDiscrete Semiconductor ProductsCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackagei4-Pac?-3SeriesHiPerFRED?Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Manufacturer Part Number	DSEE55-24N1F
Diodes - Rectifiers - ArraysPackagei4-Pac?-3SeriesHiPerFRED?Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Manufacturer	IXYS
Packagei4-Pac?-3SeriesHiPerFRED?Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Category	Discrete Semiconductor Products
SeriesHiPerFRED?Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Series ConnectionDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Package	i4-Pac?-3
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Series	HiPerFRED?
Voltage - DC Reverse (Vr) (Max)1200VCurrent - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ Vr1mA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Diode Configuration	1 Pair Series Connection
Current - Average Rectified (Io) (per Diode)60AVoltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If2.45V @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Voltage - DC Reverse (Vr) (Max)	1200V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Current - Average Rectified (Io) (per Diode)	60A
Reverse Recovery Time (trr)220nsCurrent - Reverse Leakage @ Vr1mA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Voltage - Forward (Vf) (Max) @ If	2.45V @ 60A
Current - Reverse Leakage @ VrImA @ 1200VOperating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 175°CMounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Reverse Recovery Time (trr)	220ns
Nounting TypeThrough HolePackage / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Current - Reverse Leakage @ Vr	1mA @ 1200V
Package / Casei4-Pac?-3Supplier Device Packagei4-PAC?	Operating Temperature - Junction	-55°C ~ 175°C
Supplier Device Package i4-PAC?	Mounting Type	Through Hole
	Package / Case	i4-Pac?-3
Report errors?	Supplier Device Package	i4-PAC?
		Report errors?

#### **DSEE55-24N1F** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DSEE55-24N1F Payment Methods**



## **DSEE55-24N1F** Shipping Methods



If you have any question about DSEE55-24N1F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com