



DSP1-L2-DC12V-F Information



For Reference Only

Part Number DSP1-L2-DC12V-F
Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DSP1-L2-DC12V-F Specifications

Manufacturer Part NumberDSP1-L2-DC12V-FManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	DSP1-L2-DC12V-F
Package-SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current25mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 25mA Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current25mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	DSP
Coil Current Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	25mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 5A 250VAC, 30VDC - Max 9.6 VDC 10ms - 10ms Formination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 250VAC, 30VDC - Max 9.6 VDC	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) 7	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 30VDC - Max
Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

DSP1-L2-DC12V-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DSP1-L2-DC12V-F Payment Methods



















DSP1-L2-DC12V-F Shipping Methods













If you have any question about DSP1-L2-DC12V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com