



DSP1-L2-DC24V Information



For Reference Only

Part Number DSP1-L2-DC24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DSP1-L2-DC24V Specifications

Manufacturer Part NumberDSP1-L2-DC24VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - Fully		
CategoryRelaysPackage-SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - Fully	Manufacturer Part Number	DSP1-L2-DC24V
Package - Series DSP Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Manufacturer	Panasonic Electric Works
Package - DSP Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Category	Relays
SeriesDSPRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesSealed - Fully		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Package	-
Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Series	DSP
Coil Current 12.5mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Coil Type	Latching, Dual Coil
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Coil Current	12.5mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Sealed - Fully	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 5ms Features Sealed - Fully	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully	Switching Voltage	250VAC, 30VDC - Max
Operate Time10msRelease Time5msFeaturesSealed - Fully	Turn On Voltage (Max)	19.2 VDC
Release Time 5ms Features Sealed - Fully	Turn Off Voltage (Min)	-
Features Sealed - Fully	Operate Time	10ms
·	Release Time	5ms
Mounting Type	Features	Sealed - Fully
Mounting Type Tillough Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

DSP1-L2-DC24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DSP1-L2-DC24V Payment Methods



















DSP1-L2-DC24V Shipping Methods













If you have any question about DSP1-L2-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com