

DST-2-16

DST-2-16 Information



| Part Number | DST-2-16 | |
|--------------|--|--|
| Manufacturer | Signal Transformer | |
| Category | Transformers Power Transformers | |
| Description | XFRMR LAMINATED 1.1VA THRU HOLE | |
| Package | - | |
| | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com | |



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DST-2-16 Specifications

| Manufacturer Part Number DST-2-16 Manufacturer Signal Transformer Category Transformers Package - Series DST Type Laminated Core Voltage - Primary I15V, 230V Voltage - Secondary (Full Load) Parallel 8V, Series 16V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Power - Max 1.1 VA Mounting Type Prinary Hole Yoltage - Solation Scondary Hole Youtge - Solation Scondary Hole | | |
|---|---------------------------------|-----------------------------|
| CategoryTansformersPower TransformersPackagePackageSeriesDSTTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleSize / DimensionSecondaru & Secondaru & SecondaruSize / DimensionSecondaru & SecondaruMouting TypeSecondaruMounting TypeSecondaruMounting TypeSecondaruSize / DimensionSecondaruSize / DimensionSecondaruHeight - Sectod (Max)SecondaruWithger - SolationSecondaruWeightSecondaru | Manufacturer Part Number | DST-2-16 |
| Power TransformersPackage-SeriesDSTTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleSize / Dimension34.90mm Lx 28.60mm WHeight - Seated (Max)2500VrmsVoltage - Isolation2500VrmsWeight0.17 Ib (77.11g) | Manufacturer | Signal Transformer |
| Package-SeriesDSTTypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StyleSel 4.00mm L x 28.60mm WSize / Dimension24.60mmVoltage - IsolationStorVrmsWeight0.17 lb (77.11g) | Category | Transformers |
| SeriesDSTTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleStez / DimensionS4.90mm L x 28.60mm WSize / Dimension24.60mmVoltage - Isolation500VrmsWeight0.17 lb (77.11g) | | Power Transformers |
| TypeLaninated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypePrinagh HoleStez / DimensionSecondary Minding(s)Size / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)Secondary Minding(s)Wight0.17 lb (77.11g) | Package | - |
| Voltage - PrimaryInstructionVoltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)2500VrmsWoitge - Isolation0.17 lb (77.11g) | Series | DST |
| Voltage - Secondary (Full Load)Parallel 8V, Series 16VCurrent - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)2500VrmsVoltage - Isolation0.17 lb (77.11g) | Туре | Laminated Core |
| Current - Output (Max)Parallel 140mA, Series 70mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)2500VrmsVoltage - Isolation0.17 lb (77.11g) | Voltage - Primary | 115V, 230V |
| Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)2500VrmsVoltage - Isolation500VrmsWeight0.17 lb (77.11g) | Voltage - Secondary (Full Load) | Parallel 8V, Series 16V |
| Secondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)24.60mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Current - Output (Max) | Parallel 140mA, Series 70mA |
| Center TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)24.60mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Primary Winding(s) | Dual |
| Power - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)24.60mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Secondary Winding(s) | Dual |
| Mounting TypeThrough HoleTermination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)24.60mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Center Tap | No |
| Termination StylePC PinSize / Dimension34.90mm L x 28.60mm WHeight - Seated (Max)24.60mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Power - Max | 1.1 VA |
| Size / Dimension 34.90mm L x 28.60mm W Height - Seated (Max) 24.60mm Voltage - Isolation 2500Vrms Weight 0.17 lb (77.11g) | Mounting Type | Through Hole |
| Height - Seated (Max)24.60mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Termination Style | PC Pin |
| Voltage - Isolation2500VrmsWeight0.17 lb (77.11g) | Size / Dimension | 34.90mm L x 28.60mm W |
| Weight 0.17 lb (77.11g) | Height - Seated (Max) | 24.60mm |
| | Voltage - Isolation | 2500Vrms |
| Report errors? | Weight | 0.17 lb (77.11g) |
| | | Report errors? |

DST-2-16 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DST-2-16, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com