

DST-7-20 Information



For Reference Only

Part Number DST-7-20

Manufacturer Signal Transformer Category Transformers

Power Transformers

Description XFRMR LAMINATED 36VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DST-7-20 Specifications

Manufacturer Part Number Manufacturer Category Transformers Power Transformers Power Transformers Power Transformers Series DST Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Report errors?		
Category Transformers Power Transformers Package - Series DST Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 3.6A, Series 1.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Manufacturer Part Number	DST-7-20
Package Power Transformers Package Poseries DST Type Laminated Core Voltage - Primary Parallel 10V, Series 20V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Secondary Primary Winding(s) Dual Center Tap No Power - Max A6 (A70mm L x 55.50mm W Voltage - Isolation Voltage - Isolation Voltage - Isolation Power Transformers Laminated Core Laminated Core Laminated Core Day Haminated Core Laminated Core Day Through 10V, Series 20V Parallel 1	Manufacturer	Signal Transformer
Package - Series DST Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 3.6A, Series 1.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Category	Transformers
SeriesDSTTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 3.6A, Series 1.8APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.70mm L x 55.50mm WHeight - Seated (Max)40.40mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 3.6A, Series 1.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 3.6A, Series 1.8A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 1.1 lbs (499g)	Series	DST
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 3.6A, Series 1.8A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 10V, Series 20V Parallel 10V, Series 1.8A Primary Winding(s) Dual Secondary Winding(s) A	Туре	Laminated Core
Current - Output (Max)Parallel 3.6A, Series 1.8APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.70mm L x 55.50mm WHeight - Seated (Max)40.40mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Dual No 1.1 lbs (499g)	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.70mm L x 55.50mm WHeight - Seated (Max)40.40mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	Parallel 3.6A, Series 1.8A
Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 36 VA 40.40mm 40.40mm 40.40mm 1.1 lbs (499g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Center Tap	No
Termination Style PC Pin Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Power - Max	36 VA
Size / Dimension 66.70mm L x 55.50mm W Height - Seated (Max) 40.40mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Veight 40.40mm 2500Vrms 1.1 lbs (499g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Size / Dimension	66.70mm L x 55.50mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	40.40mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
Topon on one		Report errors?

DST-7-20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DST-7-20 Payment Methods





















DST-7-20 Shipping Methods













If you have any question about DST-7-20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com