

DST2-10B41 Information

Heisener.com

Part Number DST2-10B41

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 1.1VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DST2-10B41 Specifications

Manufacturer DST2-10B41 Manufacturer Pulse Electronics Power Category Transformers Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm Voltage - Isolation 2500Vrms		
CategoryTransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension28.70mm L x 28.70mm WHeight - Seated (Max)23.86mm	Manufacturer Part Number	DST2-10B41
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Manufacturer	Pulse Electronics Power
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 25.86mm	Category	Transformers
Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max)	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style Size / Dimension Peight - Seated (Max) Parallel 220mA, Series 110mA Dual Pual Pual	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) Dual No 23.86mm	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension28.70mm L x 28.70mm WHeight - Seated (Max)23.86mm	Current - Output (Max)	Parallel 220mA, Series 110mA
Center TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension28.70mm L x 28.70mm WHeight - Seated (Max)23.86mm	Primary Winding(s)	Dual
Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Center Tap	No
Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Power - Max	1.1 VA
Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Mounting Type	Through Hole
Height - Seated (Max) 23.86mm	Termination Style	PC Pin
-	Size / Dimension	28.70mm L x 28.70mm W
Voltage - Isolation 2500Vrms	Height - Seated (Max)	23.86mm
101mgC 1501mton 2500 11m5	Voltage - Isolation	2500Vrms
Weight 0.17 lb (77.11g)	Weight	0.17 lb (77.11g)
Report errors?		Report errors?

DST2-10B41 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DST2-10B41 Payment Methods



















DST2-10B41 Shipping Methods













If you have any question about DST2-10B41, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com