

## **DST2-28B46 Information**

Heisener.com

Part Number DST2-28B46

Manufacturer Pulse Electronics Power

Category Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 1.1VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DST2-28B46 Specifications**

Manufacturer Part NumberDST2-28B46ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 14V, Series 28VCurrent - Output (Max)Parallel 80mA, Series 40mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension28.70mm L x 28.70mm WHeight - Seated (Max)23.86mmVoltage - Isolation2500Vrms		
Category Power Transformers Package Package Split Bobbin Plug-In Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max No Power - Max No Mounting Type Termination Style Size / Dimension Package Power Transformers Power Ada Primary Winding(s) Pual Power Tap No Power - Max Primary Winding(s) Power	Manufacturer Part Number	DST2-28B46
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 80mA, Series 40mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max)	Manufacturer	Pulse Electronics Power
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 80mA, Series 40mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Category	Transformers
Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 14V, Series 28V Current - Output (Max) Parallel 80mA, Series 40mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 1.1 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 14V, Series 28V  Current - Output (Max) Parallel 80mA, Series 40mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 1.1 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 28.70mm L x 28.70mm W  Height - Seated (Max) 23.86mm	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 14V, Series 28V  Current - Output (Max)  Parallel 80mA, Series 40mA  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  1.1 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  Height - Seated (Max)  115V, 230V  Parallel 14V, Series 28V  Parallel 80mA, Series 40mA  In Ual  Parallel 80mA, Series 40mA  Parallel 14V, Series 28V  Parallel 14V, Series	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 80mA, Series 40mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  1.1 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  Parallel 14V, Series 28V  Parallel 14V, Series 28V  Parallel 14V, Series 28V  Pual  Pual  No  1.1 VA  Secondary Winding(s)  Pual  No  1.1 VA  Mounting Type  Through Hole  PC Pin  Size / Dimension  28.70mm L x 28.70mm W  Height - Seated (Max)  23.86mm	Type	Laminated Core
Current - Output (Max)  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  1.1 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  Peight - Seated (Max)  Parallel 80mA, Series 40mA  Dual  Pual  Pual  Pual  Pual  Power - Mo  28.70mm L x 28.70mm W  23.86mm	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  1.1 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  28.70mm L x 28.70mm W  Height - Seated (Max)	Voltage - Secondary (Full Load)	Parallel 14V, Series 28V
Secondary Winding(s)  Center Tap  No  Power - Max  1.1 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  28.70mm L x 28.70mm W  Height - Seated (Max)  23.86mm	Current - Output (Max)	Parallel 80mA, Series 40mA
Center Tap No  Power - Max 1.1 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 28.70mm L x 28.70mm W  Height - Seated (Max) 23.86mm	Primary Winding(s)	Dual
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  28.70mm L x 28.70mm W  Height - Seated (Max)  23.86mm	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension28.70mm L x 28.70mm WHeight - Seated (Max)23.86mm	Center Tap	No
Termination Style PC Pin Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Power - Max	1.1 VA
Size / Dimension 28.70mm L x 28.70mm W Height - Seated (Max) 23.86mm	Mounting Type	Through Hole
Height - Seated (Max) 23.86mm	Termination Style	PC Pin
	Size / Dimension	28.70mm L x 28.70mm W
Voltage - Isolation 2500Vrms	Height - Seated (Max)	23.86mm
1 offage 1 solution 2,500 1 ms	Voltage - Isolation	2500Vrms
Weight 0.17 lb (77.11g)	Weight	0.17 lb (77.11g)
Report errors?		Report errors?

#### **DST2-28B46** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **DST2-28B46 Payment Methods**



















## **DST2-28B46 Shipping Methods**













If you have any question about DST2-28B46, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com