

### **DST3-20B13 Information**

Heisener.com

Part Number DST3-20B13

Manufacturer Pulse Electronics Power

Category Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 2.4VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **DST3-20B13 Specifications**

Manufacturer Part NumberDST3-20B13ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 240mA, Series 120mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2.4 VAMounting TypeThrough HoleTermination StylePC Pin		
Category  Transformers  Power Transformers  Package  Series  Split Bobbin Plug-In  Type  Laminated Core  Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 10V, Series 20V  Current - Output (Max)  Parallel 240mA, Series 120mA  Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Through Hole	Manufacturer Part Number	DST3-20B13
Power Transformers  Package  Series  Split Bobbin Plug-In  Type  Laminated Core  Voltage - Primary  115V, 230V  Voltage - Secondary (Full Load)  Parallel 10V, Series 20V  Current - Output (Max)  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Power Transformers	Manufacturer	Pulse Electronics Power
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 240mA, Series 120mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.4 VA Mounting Type Through Hole	Category	Transformers
Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 240mA, Series 120mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.4 VA Mounting Type Through Hole		Power Transformers
Type  Voltage - Primary  Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Perallel 240mA, Series 120mA  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Laminated Core  Laminated Core  Nover - Max  Parallel 10V, Series 20V  Parallel 240mA, Series 120mA  No  Dual  Through Hole	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Pual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  115V, 230V  Parallel 10V, Series 20V  Parallel 240mA, Series 120mA  Dual  Dual  No  Through Hole	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Parallel 10V, Series 20V  Parallel 240mA, Series 120mA  Dual  Dual  No  Through Hole	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max August 2.4 VA Mounting Type Through Hole	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Dual  No  2.4 VA  Through Hole	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Dual  No  2.4 VA  Through Hole	Current - Output (Max)	Parallel 240mA, Series 120mA
Center Tap No Power - Max 2.4 VA Mounting Type Through Hole	Primary Winding(s)	Dual
Power - Max 2.4 VA  Mounting Type Through Hole	Secondary Winding(s)	Dual
Mounting Type Through Hole	Center Tap	No
	Power - Max	2.4 VA
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Size / Dimension 35.05mm L x 28.70mm W	Size / Dimension	35.05mm L x 28.70mm W
Height - Seated (Max) 30.23mm	Height - Seated (Max)	30.23mm
Voltage - Isolation 2500Vrms	Voltage - Isolation	2500Vrms
Weight 0.25 lb (113.4g)	Weight	0.25 lb (113.4g)
Report errors?		Report errors?

#### **DST3-20B13 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **DST3-20B13 Payment Methods**


































If you have any question about DST3-20B13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com