

DST4-56B34 Information

Heisener.com

Part Number DST4-56B34

Manufacturer Pulse Electronics Power

Category Transformers

Power Transformers

Description XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DST4-56B34 Specifications

Manufacturer Part Number Manufacturer Pulse Electronics Power Transformers Power Transformers Package - Series Split Bobbin Plug-In Laminated Core Voltage - Primary Voltage - Perimary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Light Sected (Max) Pulse Electronics Power Transformers Power Transformers Power Transformers Power Transformers Power Transformers Power - Max All (All Mark) Parallel 220mA, Series 110mA Power - Max No 41.40mm L x 33.27mm W Pusight Sected (Max)		
Category Transformers Power Transformers Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension Tansformers Power Transformers Inasterior Transes Power Transformers Power Transformers Power Transformers Power Transformers Paper Inaster Transes Power Transformers Powe	Manufacturer Part Number	DST4-56B34
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W	Manufacturer	Pulse Electronics Power
Package - Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W	Category	Transformers
Series Split Bobbin Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension 115V, 230V Parallel 28V, Series 56V Parallel 220mA, Series 110mA Pual Pual A Unit Type Through Hole PC Pin Size / Dimension 41.40mm L x 33.27mm W	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 220mA, Series 110mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Parallel 28V, Series 56V Parallel 220mA, Series 110mA Dual Dual No Poul No Poul Through Hole PC Pin 41.40mm L x 33.27mm W	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Parallel 220mA, Series 110mA Dual Through Power Series 110mA Dual Through Power Series 110mA Power Series 110mA Dual Power Series 110mA Power Series 110mA Poul Ser	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Dual No 41.40mm L x 33.27mm W	Voltage - Secondary (Full Load)	Parallel 28V, Series 56V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.40mm L x 33.27mm W	Current - Output (Max)	Parallel 220mA, Series 110mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.40mm L x 33.27mm W	Primary Winding(s)	Dual
Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W	Center Tap	No
Termination Style PC Pin Size / Dimension 41.40mm L x 33.27mm W	Power - Max	6 VA
Size / Dimension 41.40mm L x 33.27mm W	Mounting Type	Through Hole
	Termination Style	PC Pin
Height Costed (May)	Size / Dimension	41.40mm L x 33.27mm W
rieigii - Sealed (Max) 33.2/mm	Height - Seated (Max)	33.27mm
Voltage - Isolation 2500Vrms	Voltage - Isolation	2500Vrms
Weight 0.44 lb (199.58g)	Weight	0.44 lb (199.58g)
Report errors?		Report errors?

DST4-56B34 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DST4-56B34 Payment Methods





















DST4-56B34 Shipping Methods













If you have any question about DST4-56B34, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com