

DST7-36B57

DST7-36B57 Information

•	Heisener.com	 DST7-36B57 Pulse Electronics Power Transformers Power Transformers XFRMR LAMINATED 36VA THRU HOLE - For the pricing/inventory/lead time, please contact	
]	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DST7-36B57 Specifications

Manufacturer Part NumberDST7-36B57ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)DualSecondary Winding(s)DualPower - Max36 VAPower - MaxSteriesMounting TypeThrough HoleSterier TapPrinaryHeight - Seated (Max)36.20mm KVoltage - Dimension39.62mm		
CategoryTransformersPackage-Package-SeriesSplit Bobin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)DualPrimary Winding(s)DualSecondary Winding(s)SolPower - Max36 VAPower - MaxSecondary (Full Load)Primation StyleDensityHounting TypeSolHounting TypeSolPrimation StyleSolHeight - Seared (Max)39.62mm	Manufacturer Part Number	DST7-36B57
Power TransformersPackage-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualPower - Max36 VAPower - MaxSecondary IPIntropy FullPrincy HulePrimation StyleCP inHeight - Seated (Max)9.62mm	Manufacturer	Pulse Electronics Power
Package-Package-SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension680mm Lx 55.63mm WHeight - Seated (Max)39.62mm	Category	Transformers
SeriesSplit Bobbin Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Package	-
SyrInformationVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Series	Split Bobbin Plug-In
Voltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Туре	Laminated Core
Current - Output (Max)Parallel 2A, Series 1APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Current - Output (Max)	Parallel 2A, Series 1A
Center TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Primary Winding(s)	Dual
Power - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Center Tap	No
Termination StylePC PinSize / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Power - Max	36 VA
Size / Dimension66.80mm L x 55.63mm WHeight - Seated (Max)39.62mm	Mounting Type	Through Hole
Height - Seated (Max) 39.62mm	Termination Style	PC Pin
-	Size / Dimension	66.80mm L x 55.63mm W
Voltage Isolation 2500Vrms	Height - Seated (Max)	39.62mm
	Voltage - Isolation	2500Vrms
Weight 1.1 lbs (499g)	Weight	1.1 lbs (499g)
Report errors		Report errors?

DST7-36B57 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about DST7-36B57, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com